

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER PRIZA, NEW UNICA, MECANISM CU RAMA FIXARE, 2P E,
16A, SCHUKO, CU OBTURATSAU, VOPSIT, ANTRACIT**

Schneider Electric New Unica socket-outlet NU503754D is a mechanism with zamak fixing frame in color anthracite. The outlet pole configuration of this socket-outlet is 2P + E with shutters, protecting the children from possible electricity shock. And this device is German standard. The dielectric strength of this socket-outlet is 2000 V. And its rated current is 16A. The fixing mode of this device is screws or claws. It is 74.5 mm in width, 74.5 mm in height, 40 mm in depth, with an embedding depth of 30.5 mm. The surface finish is matt, gaining extra point for your interior design. Its protection degree is IP21D. Besides, it reaches IK04 protection level, which can help protect against impact. The connection terminals of this socket-outlet are screw terminals. Being made of PC material, this socket-outlet is quite reliable and resistant. It obtained AENOR, EAC certificate as well. And it is mercury free as well as heavy metal free, taking care of the environment and your health all the time. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism with zamak fixing frame

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - Screws or claws

Colour tint - Anthracite (RAL 7021)

Connections - terminals - Screw terminals

Cable cross section - 0.5-1.5 mm² cable(s), 2 - cable stiffness: flexible

0.5-1.5 mm² cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 MΩ at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

PC (polycarbonate) GF10 FR: casing

Zamak: fixing frame

Surface finish - Painted

Quantity per set - Set of 1 flow-pack

Standards - IEC 60884-1

UNE 20315-1-1

UNE 20315-1-2

DIN VDE 0620-1

Product certifications - EAC

AENOR

Embedding depth - 30.5 mm

Depth - 40 mm

Width - 74.5 mm

Height - 74.5 mm

Net weight - 0.0665 kg

Surface treatment - Painted

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 to 35 A°C

Ambient air temperature for storage - -5 to 50 A°C

IK degree of protection - IK04

IP degree of protection - IP21D

Environmental characteristic - Acetone

Bleach

UV resistant

Petrol

Oil
Alcohol
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.0 cm
Package 1 Width - 4.5 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 75.0 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 10.3 cm
Package 2 Width - 13.7 cm
Package 2 Length - 37.5 cm
Package 2 Weight - 825.0 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 100
Package 3 Height - 30.0 cm
Package 3 Width - 40.0 cm
Package 3 Length - 60.0 cm
Package 3 Weight - 8.953 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/priza-new-unica-mecanism-cu-rama-fixare-2p-e-16a-schuko-cu-obturatsau-vopsit-antracit-318876>