

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER AMERICAN PRIZA DUBLA, NEW UNICA,  
 OBTURATSAUOSU, 15 A, 3 MODULE, ALB**

Schneider Electric New Unica socket-outlet NU306018 is a mechanism in color white with 2 socket outlets. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. And this device is American standard. The dielectric strength level, namely the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown or electrical discharge, is 2000V. Its rated current is 15A. The device's fixing mode is clip-in. It is 45 mm in width, 45 mm in height and 35 mm in depth with an embedding depth of 26 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is brilliant, gaining extra point for your interior design. It reaches IP20 degree of protection which is very high. It reaches IK01 protection level, which can help protect against impact. Its connection terminals are screw terminals. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica  
 Device application - Power supply  
 Product or component type - Socket-outlet  
 device presentation - Mechanism  
 Socket number - 2  
 Outlet poles configuration - 2P + E  
 outlet standard - American  
 Outlet standard description - Centred earth  
 Complementary  
 Cover type - With shutter  
 device mounting - Flush  
 Rated current - 15 A  
 [Ue] rated operational voltage - 250 V  
 Network type - AC  
 Network frequency - 50/60 Hz  
 Number of modules - 3 modules  
 Fixing mode - Clip-in  
 Colour tint - White (RAL 9003)  
 Connections - terminals - Screw terminals  
 Cable cross section - 0.4 mm<sup>2</sup> - cable stiffness: flexible  
 0.4 mm<sup>2</sup> - cable stiffness: rigid  
 Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6  
 Electrical durability - 10000 cycles, cos phi = 0.8  
 Insulation resistance - > 5 MΩ at 500 V  
 Dielectric strength - 2000 V  
 Material - PC: mechanism cover  
 PC (polycarbonate) GF10 FR: casing  
 Surface finish - Glossy  
 Quantity per set - Set of 1 flow-pack  
 Standards - IEC 60884-1  
 Embedding depth - 26 mm  
 Depth - 30 mm  
 Width - 67.5 mm  
 Height - 45 mm  
 Net weight - 0.036 kg  
 Surface treatment - Untreated  
 Resistance to chemical agents - Resistant to alcohol (70 %)  
 Resistant to alcohol (96 %)  
 Resistant to A-Lactic Acid  
 Resistant to diluted quaternary ammonium  
 Resistant to diluted bleach  
 Resistant to diluted ammonia  
 Resistant to soapy water  
 Resistant to crystal cleaner  
 Resistant to hydrogen peroxide 10 volumes  
 Resistant to hexane  
 Environment  
 Ambient air temperature for operation - -5 to 35 A°C  
 Ambient air temperature for storage - -5 to 50 A°C  
 IK degree of protection - IK01  
 IP degree of protection - IP20  
 Environmental characteristic - UV resistant  
 Acetone  
 Window-cleaning fluid  
 Alcohol  
 Oil  
 Liquid soap  
 Bleach  
 Petrol  
 Packing Units  
 Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1  
Package 1 Height - 2.95 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 6.75 cm  
Package 1 Weight - 36 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 5  
Package 2 Height - 6.5 cm  
Package 2 Width - 12 cm  
Package 2 Length - 18.5 cm  
Package 2 Weight - 248.3 g  
Unit Type of Package 3 - S04  
Number of Units in Package 3 - 180  
Package 3 Height - 30 cm  
Package 3 Width - 40 cm  
Package 3 Length - 60 cm  
Package 3 Weight - 9.642 kg  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/american-priza-dubla-new-unica-obturatsausu-15-a-3-module-alb-318921>