

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER CONNECTED SINGLE PRIZA, NEW UNICA, 16 A, SCHUKO, ANTRACIT

Schneider Electric Wiser New Unica connected socket outlet with power supply application. The outlet pole configuration of this socket-outlet is 2P+E with shutters. The device respects the German (side earth) Outlet standard. This product is compatible with Amazon Alexa (EF014927), Apple HomeKit (EF014925), Google Assistant (EF014926). The device is with 2 modules and fixed with 4 fixing points. The fixing frame of the device is Zamak. Easy installation, screwdriver is not required to connect the cables, thanks to the screwless connection. The operating voltage of 220-240VAC and rated current of 16A with a frequency 50/60Hz. Its has dielectric strength of 2000V. The Socket Outlet is compatible with 3680W Resistive load, 16A Inductive load, and 6AX Capacitive load. The rated Insulation voltage is 500V with an insulation resistance of greater than 5M Ω . This device enables flush mounting. The dimensions are (W) 74.5mm x (H) 74.5mm x (D) 40mm and have a 30.5mm Embedding depth. It weighs 73.9g. The color of this device is anthracite (RAL 7021) with a matt finish and is made of polycarbonate. The operating temperature is from -5 $^{\circ}$ C up to +35 $^{\circ}$ C and the storage temperature is from -5 $^{\circ}$ C up to +50 $^{\circ}$ C. It reaches IK05 and IP20 degrees of protection. This product comes in a set of 1 Box carton packaging. Delivered in set of 1 Box packaging. To be completed with the cover frame. The device is fixed with 4 fixing points. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Users benefit from beautiful design that match their style and innovative products. New Unica features innovative functions to carry the range into the smart homes of the future. This device is compliant with the standards of IEC 60884-1, UNE 20315-1-1, and UNE 20315-1-2 and with EAC certifications. Main

Range - New Unica

Product or component type - Connected socket-outlet

device presentation - Mechanism with fixing frame

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 220...240 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 2 modules

Fixing mode - 4 fixing points

Colour tint - Anthracite (RAL 7021)

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm 2 cable(s), 2 - cable stiffness: flexible

0.5-2.5 mm 2 cable(s), 2 - cable stiffness: rigid

Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6

Electrical durability - 10000 cycles, cos phi = 0.8

Insulation resistance - > 5 M Ω at 500 V

Dielectric strength - 2000 V

Material - PC: mechanism cover

Zamak: fixing frame

PC (polycarbonate) GF10 FR: casing

Surface finish - Matt

Quantity per set - Set of 1 box

Standards - IEC 60884-1

UNE 20315-1-1

UNE 20315-1-2

Product certifications - EAC

Embedding depth - 30.5 mm

Depth - 40 mm

Width - 74.5 mm

Height - 74.5 mm

Net weight - 0.0739 kg

Surface treatment - Painted

Type of packing - Carton

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

Ambient air temperature for operation - -5 $^{\circ}$ C; 35 $^{\circ}$ C

Ambient air temperature for storage - -5a€!50 A°C
IK degree of protection - IK05
IP degree of protection - IP20
Environmental characteristic - Acetone
UV resistant
Petrol
Oil
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 7.9 cm
Package 1 Width - 9.5 cm
Package 1 Length - 9.5 cm
Package 1 Weight - 170.0 g
Unit Type of Package 2 - S03
Number of Units in Package 2 - 36
Package 2 Height - 30.0 cm
Package 2 Width - 30.0 cm
Package 2 Length - 40.0 cm
Package 2 Weight - 6.612 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/connected-single-priza-new-unica-16-a-schuko-antracit-318937>