

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTERRUPATOR, NEW UNICA, 1-POLE 1-WAY, 10AX, 1  
 MODULE, TERMINAL FARA SURUBURI, VOPSIT, IP4X, ANTRACIT**

Schneider Electric New Unica switch NU310154 is a mechanism in color anthracite. This is a 1-pole 1-way switch. The device's fixing mode is clip-in. Its rated current is 10AX. It is 22.5 mm in width, It is 45 mm in height, 34.25 mm in depth with an embedding depth of 21.15 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. Its connection terminals are screwless terminals. Cu.Zn37, PBT (polybutylene terephthalate) GF30, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized It obtained AENOR, CE, EAC, NF certificate. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

- Range of product - New Unica
- Product or component type - Switch
- device presentation - Mechanism
- Technology type - Electromechanical
- Switch function - 1-pole 1-way
- Number of rocker - 1
- Device application - Light control
- Colour tint - Anthracite (RAL 7021)
- Type of packing - Flow-pack
- Complementary
- Rated current - 10 AX
- [Ue] rated operational voltage - 250 V
- Network type - AC
- Network frequency - 50/60 Hz
- Electrical durability - 20000 cycles, cos phi = 0.6
- Insulation resistance - > 5 MOhm at 500 V
- Dielectric strength - 2000 V
- Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3
- Opening distance - > 3 mm
- Actuator - Rocker
- Number of modules - 1 module
- Connections - terminals - Screwless terminals
- Cable cross section - 0.5-2.5 mm<sup>2</sup> rigid cable
- 0.5-2.5 mm<sup>2</sup> flexible cable
- Material - Thermoplastic ABS-UV stabilised: mechanism rocker
- PC (polycarbonate) GF10 FR: casing
- CuZn37: terminals
- PBT (polybutylene terephthalate) GF30: release button
- Marking - Without marking
- Surface finish - Matt
- specific treatment - integrated within the material - Painted
- Fixing mode - Clip-in
- Width - 22.5 mm
- Height - 45 mm
- Depth - 34.25 mm
- Embedding depth - 21.15 mm
- Net weight - 0.0147 kg
- Ambient air temperature for operation - -5 to +40 A°C
- Ambient air temperature for storage - -5 to +50 A°C
- Standards - EN 60669-1
- LV directive
- EMC directive
- Product certifications - AENOR
- NF
- VDE
- EAC
- CE
- Resistance to chemical agents - Resistant to alcohol (70 %)
- Resistant to alcohol (96 %)
- Resistant to A-Lactic Acid
- Resistant to diluted quaternary ammonium
- Resistant to diluted bleach
- Resistant to diluted ammonia
- Resistant to soapy water
- Resistant to crystal cleaner
- Resistant to hydrogen peroxide 10 volumes
- Resistant to hexane
- Environment
- IP degree of protection - IP4X
- IK degree of protection - IK04
- Environmental characteristic - Oil
- UV resistant
- Acetone
- Liquid soap
- Window-cleaning fluid

Petrol  
Alcohol  
Bleach  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 2.3 cm  
Package 1 Width - 3.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 15 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 20  
Package 2 Height - 8.2 cm  
Package 2 Width - 17.7 cm  
Package 2 Length - 18.5 cm  
Package 2 Weight - 384 g  
Unit Type of Package 3 - S03  
Number of Units in Package 3 - 160  
Package 3 Height - 30 cm  
Package 3 Width - 30 cm  
Package 3 Length - 40 cm  
Package 3 Weight - 3.559 kg  
Pret: 15,46 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-1-pole-1-way-10ax-1-module-terminal-fara-suruburi-vopsit-ip4x-antracit-318971>