

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTRERUPATOR, NEW UNICA, MECANISM, 1-POLE 2-  
WAY, 16AX, 1 MODULE, SCREW TERMINALS, VOPSIT, IP4X,  
ANTRACIT**

Schneider Electric New Unica switch NU316354 is a mechanism in color anthracite. This is a 1-pole 2-way switch. The fixing mode of this device is clip-in. Its rated current is 16AX. It is 22.5 mm in width, It is 45 mm in height, 34.25 mm in depth with an embedding depth of 21.15 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. This switch has screw terminals connection terminals. The switch is made of Cu.Zn15, Cu.Zn5 Ag, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized, making it as resistant as possible. It obtained AENOR, CE, EAC, NF certificate. Being environmentally friendly, this switch is a green premium product. It is mercury free as well as heavy metal free, taking care of the environment and your health. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica  
Product or component type - Switch  
device presentation - Mechanism  
Technology type - Electromechanical  
Switch function - 1-pole 2-way  
Number of rocker - 1  
Device application - Light control  
Colour tint - Anthracite (RAL 7021)  
Type of packing - Flow-pack  
Complementary  
Rated current - 16 AX  
[Ue] rated operational voltage - 250 V  
Network type - AC  
Network frequency - 50/60 Hz  
Electrical durability - 20000 cycles, cos phi = 0.6  
Insulation resistance - > 5 MOhm at 500 V  
Dielectric strength - 2000 V  
Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3  
Opening distance - > 3 mm  
Actuator - Rocker  
Number of modules - 1 module  
Connections - terminals - Screw terminals  
Cable cross section - 0.4 mm<sup>2</sup> rigid cable  
0.4 mm<sup>2</sup> flexible cable  
Material - CuZn15: fixed terminals  
CuZn5 Ag: mobile contact  
Thermoplastic ABS-UV stabilised; mechanism rocker  
PC (polycarbonate) GF10 FR: casing  
Marking - Without marking  
Surface finish - Matt  
specific treatment - integrated within the material - Painted  
Fixing mode - Clip-in  
Width - 22.5 mm  
Height - 45 mm  
Depth - 34.25 mm  
Embedding depth - 21.15 mm  
Net weight - 0.0179 kg  
Ambient air temperature for operation - -5 to 40 °C  
Ambient air temperature for storage - -5 to 50 °C  
Standards - EN 60669-1  
LV directive  
EMC directive  
Product certifications - CE  
AENOR  
EAC  
NF  
VDE  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IP degree of protection - IP4X  
IK degree of protection - IK04  
Environmental characteristic - Oil  
UV resistant

Acetone  
Liquid soap  
Window-cleaning fluid  
Petrol  
Alcohol  
Bleach

Packing Units

Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 2.3 cm  
Package 1 Width - 3.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 20.0 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 20  
Package 2 Height - 8.0 cm  
Package 2 Width - 18.0 cm  
Package 2 Length - 18.5 cm  
Package 2 Weight - 482.0 g  
Unit Type of Package 3 - S02  
Number of Units in Package 3 - 40  
Package 3 Height - 15.0 cm  
Package 3 Width - 30.0 cm  
Package 3 Length - 40.0 cm  
Package 3 Weight - 1.27 kg  
Pret: 23,88 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-mecanism-1-pole-2-way-16ax-1-module-screw-terminals-vopsit-ip4x-antracit-318988>