

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTRERUPATOR, NEW UNICA, INTERMEDIATE, 10AX, 2
MODULE, TERMINAL FARA SURUBURI, NETRATAT, IP4X, ALB**

Schneider Electric New Unica switch NU320518 is a mechanism in color white. This is an intermediate switch. The fixing mode of this device is clip-in. Its rated current is 10AX. It is 45 mm in width, 45 mm in height 37.75 mm in depth with an embedding depth of 24.65 mm. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. Its connection terminals are screwless terminals. Cu.Zn15, Cu.Zn5 Ag, PBT (polybutylene terephthalate) GF31, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized It obtained AENOR, CE, EAC, NF certificate. As a green premium product, this device is environmentally friendly. It is mercury free. And heavy metal free, which takes care of the environment and your health as always. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica
Product or component type - Switch
device presentation - Mechanism
Technology type - Electromechanical
Switch function - Intermediate
Number of rocker - 1
Device application - Light control
Colour tint - White (RAL 9003)
Type of packing - Flow-pack
Complementary
Rated current - 10 AX
[Ue] rated operational voltage - 250 V
Network type - AC
Network frequency - 50/60 Hz
Electrical durability - 20000 cycles, cos phi = 0.6
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3
Opening distance - > 3 mm
Actuator - Rocker
Number of modules - 2 modules
Connections - terminals - Screwless terminals
Cable cross section - 0.5-2.5 mm² rigid cable
0.5-2.5 mm² flexible cable
Material - CuZn5 Ag: fixed terminals
CuZn15: mobile contact
PBT (polybutylene terephthalate) GF31: release button
Thermoplastic ABS-UV stabilised: mechanism rocker
PC (polycarbonate) GF10 FR: casing
Marking - Without marking
Surface finish - Glossy
specific treatment - integrated within the material - Untreated
Fixing mode - Clip-in
Width - 45 mm
Height - 45 mm
Depth - 37.75 mm
Embedding depth - 24.65 mm
Net weight - 0.0216 kg
Ambient air temperature for operation - -5 to 40 A°C
Ambient air temperature for storage - -5 to 50 A°C
Standards - EN 60669-1
LV directive
EMC directive
Product certifications - CE
AENOR
EAC
NF
VDE
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IP degree of protection - IP4X
IK degree of protection - IK04
Environmental characteristic - Oil
UV resistant

Acetone
Liquid soap
Window-cleaning fluid
Petrol
Alcohol
Bleach

Packing Units

Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 3.5 cm
Package 1 Width - 4.5 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 22.0 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 6.0 cm
Package 2 Width - 18.0 cm
Package 2 Length - 18.6 cm
Package 2 Weight - 322.0 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 200
Package 3 Height - 30.0 cm
Package 3 Width - 40.0 cm
Package 3 Length - 60.0 cm
Package 3 Weight - 7.233 kg
Pret: 23,41 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-intermediate-10ax-2-module-terminal-fara-suruburi-netratat-ip4x-alb-319000>