


Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTRERUPATOR, NEW UNICA, INTERMEDIATE, 10AX, 2  
 MODULE, TERMINAL FARA SURUBURI, VOPSIT, IP4X, ALUMINIU**

Schneider Electric New Unica switch NUC320530 is a mechanism in color aluminium. This is an intermediate switch. The fixing mode of this device is clip-in. Its rated current is 10AX. It is 45 mm in width, 45 mm in height and 37.75 mm in depth with an embedding depth of 24.65 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. This switch has screwless terminals connection terminals. The switch is made of Cu.Zn15, Cu.Zn5 Ag, PBT (polybutylene terephthalate) GF31, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized, making it resistant and durable. This switch is AENOR, CE, EAC, NF certified. Being environmentally friendly, this switch is a green premium product. It is mercury free. And heavy metal free, which takes care of the environment and your health as always. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.

Main  
 Range of product - New Unica  
 Product or component type - Switch  
 device presentation - Mechanism  
 Technology type - Electromechanical  
 Switch function - Intermediate  
 Number of rocker - 1  
 Device application - Light control  
 Colour tint - Aluminium  
 Type of packing - Flow-pack  
 Complementary  
 Rated current - 10 AX  
 [Ue] rated operational voltage - 250 V  
 Network type - AC  
 Network frequency - 50/60 Hz  
 Electrical durability - 20000 cycles, cos phi = 0.6  
 Insulation resistance - > 5 MOhm at 500 V  
 Dielectric strength - 2000 V  
 Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3  
 Opening distance - > 3 mm  
 Actuator - Rocker  
 Number of modules - 2 modules  
 Connections - terminals - Screwless terminals  
 Cable cross section - 0.5-2.5 mm<sup>2</sup> rigid cable  
 0.5-2.5 mm<sup>2</sup> flexible cable  
 Material - CuZn5 Ag: fixed terminals  
 CuZn15: mobile contact  
 PBT (polybutylene terephthalate) GF31: release button  
 Thermoplastic ABS-UV stabilised: mechanism rocker  
 PC (polycarbonate) GF10 FR: casing  
 Marking - Without marking  
 Surface finish - Glossy  
 specific treatment - integrated within the material - Painted  
 Fixing mode - Clip-in  
 Width - 45 mm  
 Height - 45 mm  
 Depth - 37.75 mm  
 Embedding depth - 24.65 mm  
 Net weight - 0.0216 kg  
 Ambient air temperature for operation - -5 to +40 A°C  
 Ambient air temperature for storage - -5 to +50 A°C  
 Standards - EN 60669-1  
 LV directive  
 EMC directive  
 Product certifications - CE  
 AENOR  
 EAC  
 NF  
 VDE  
 Resistance to chemical agents - Resistant to alcohol (70 %)  
 Resistant to alcohol (96 %)  
 Resistant to A-Lactic Acid  
 Resistant to diluted quaternary ammonium  
 Resistant to diluted bleach  
 Resistant to diluted ammonia  
 Resistant to soapy water  
 Resistant to crystal cleaner  
 Resistant to hydrogen peroxide 10 volumes  
 Resistant to hexane  
 Environment  
 IP degree of protection - IP4X  
 IK degree of protection - IK04  
 Environmental characteristic - Oil

UV resistant  
Acetone  
Liquid soap  
Window-cleaning fluid  
Petrol  
Alcohol  
Bleach  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 3.5 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 22.0 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10  
Package 2 Height - 8.0 cm  
Package 2 Width - 18.0 cm  
Package 2 Length - 18.6 cm  
Package 2 Weight - 322.0 g  
Unit Type of Package 3 - S04  
Number of Units in Package 3 - 200  
Package 3 Height - 30.0 cm  
Package 3 Width - 40.0 cm  
Package 3 Length - 60.0 cm  
Package 3 Weight - 7.231 kg  
Pret: 38,63 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/interruptor-new-unica-intermediate-10ax-2-module-terminal-fara-suruburi-vopsit-ip4x-aluminiu-319001>