

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTRERUPATOR, NEW UNICA, MECANISM, 2-POLE 1-WAY, 20A, 2 MODULE, SCREW TERMINALS, NETRATAT, IP4X, ALB**

Schneider Electric New Unica switch NU322518 is a mechanism in color white. This is a 2-pole 1-way switch. The fixing mode of this device is clip-in. Its rated current is 20A. It is 45 mm in width, 45 mm in height 29 mm in depth with an embedding depth of 15.5 mm. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. This switch has screw terminals connection terminals. The switch is made of thermoplastic ABS-UV stabilized, making it resistant and durable. This switch is AENOR, CE, EAC, NF certified. This device is qualified as a green premium product, with minimal use of hazardous substances. It is mercury free. And heavy metal free, which takes care of the environment and your health as always. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica  
 Product or component type - Switch  
 device presentation - Mechanism  
 Technology type - Electromechanical  
 Switch function - 2-pole 1-way  
 Number of rocker - 1  
 Device application - Light control  
 Colour tint - White (RAL 9003)  
 Type of packing - Flow-pack  
 Complementary  
 Rated current - 20 A  
 [Ue] rated operational voltage - 250 V  
 Network type - AC  
 Network frequency - 50/60 Hz  
 Electrical durability - 20000 cycles, cos phi = 0.6  
 Insulation resistance - > 5 MOhm at 500 V  
 Dielectric strength - 2000 V  
 Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3  
 Opening distance - > 3 mm  
 Actuator - Rocker  
 Number of modules - 2 modules  
 Connections - terminals - Screw terminals  
 Cable cross section - 0.5-4 mm<sup>2</sup> rigid cable  
 0.5-4 mm<sup>2</sup> flexible cable  
 Material - Thermoplastic ABS-UV stabilised: mechanism rocker  
 Marking - Without marking  
 Surface finish - Glossy  
 specific treatment - integrated within the material - Untreated  
 Fixing mode - Clip-in  
 Width - 45 mm  
 Height - 45 mm  
 Depth - 29 mm  
 Embedding depth - 15.5 mm  
 Net weight - 0.0242 kg  
 Ambient air temperature for operation - -5 to 40 A°C  
 Ambient air temperature for storage - -5 to 50 A°C  
 Standards - LV directive  
 IEC 60669-1  
 Product certifications - CE  
 Resistance to chemical agents - Resistant to alcohol (70 %)  
 Resistant to alcohol (96 %)  
 Resistant to A-Lactic Acid  
 Resistant to diluted quaternary ammonium  
 Resistant to diluted bleach  
 Resistant to diluted ammonia  
 Resistant to soapy water  
 Resistant to crystal cleaner  
 Resistant to hydrogen peroxide 10 volumes  
 Resistant to hexane  
 Environment  
 IP degree of protection - IP4X  
 IK degree of protection - IK04  
 Environmental characteristic - Oil  
 UV resistant  
 Acetone  
 Liquid soap  
 Window-cleaning fluid  
 Petrol  
 Alcohol  
 Bleach  
 Packing Units  
 Unit Type of Package 1 - PCE  
 Number of Units in Package 1 - 1

Package 1 Height - 2.5 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 25.0 g  
Unit Type of Package 2 - S02  
Number of Units in Package 2 - 20  
Package 2 Height - 15 cm  
Package 2 Width - 30 cm  
Package 2 Length - 40 cm  
Package 2 Weight - 980 g  
Pret: 38,82 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-mecanism-2-pole-1-way-20a-2-module-screw-terminals-netratat-ip4x-alb-319008>