

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTRERUPATOR, NEW UNICA, MECANISM, 1-POLE 2-
WAY, 16AX, 2 MODULE, SCREW TERMINALS, VOPSIT, IP4X,
ALUMINIU**

Schneider Electric New Unica switch NU326330 is a mechanism in color aluminium. This is a 1-pole 2-way switch. Clip-in this rocker switch for the fixation. Its rated current is 16AX. It is 45 mm in width, 45 mm in height 34.25 mm in depth with an embedding depth of 21.15 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. Its connection terminals are screw terminals. The switch is made of Cu.Zn15, Cu.Zn5 Ag, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized, making it resistant and durable. This switch is AENOR, CE, EAC, NF certified. This device is qualified as a green premium product, with minimal use of hazardous substances. It is mercury free as well as heavy metal free, taking care of the environment. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica
Product or component type - Switch
device presentation - Mechanism
Technology type - Electromechanical
Switch function - 1-pole 2-way
Number of rocker - 1
Device application - Light control
Colour tint - Aluminium
Type of packing - Flow-pack
Complementary
Rated current - 16 AX
[Ue] rated operational voltage - 250 V
Network type - AC
Network frequency - 50/60 Hz
Electrical durability - 20000 cycles, cos phi = 0.6
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3
Opening distance - > 3 mm
Actuator - Rocker
Number of modules - 2 modules
Connections - terminals - Screw terminals
Cable cross section - 0.4 mm² rigid cable
0.4 mm² flexible cable
Material - CuZn15: fixed terminals
CuZn5 Ag: mobile contact
Thermoplastic ABS-UV stabilised; mechanism rocker
PC (polycarbonate) GF10 FR: casing
Marking - Without marking
Surface finish - Glossy
specific treatment - integrated within the material - Painted
Fixing mode - Clip-in
Width - 45 mm
Height - 45 mm
Depth - 34.25 mm
Embedding depth - 21.15 mm
Net weight - 0.02 kg
Ambient air temperature for operation - -5 to 40 A°C
Ambient air temperature for storage - -5 to 50 A°C
Standards - IEC 60669-1
LV directive
Product certifications - CE
AENOR
EAC
NF
VDE
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
IP degree of protection - IP4X
IK degree of protection - IK04
Environmental characteristic - Oil
UV resistant
Acetone

Liquid soap
Window-cleaning fluid
Petrol
Alcohol
Bleach
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.0 cm
Package 1 Width - 4.5 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 21.0 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 8.0 cm
Package 2 Width - 18.0 cm
Package 2 Length - 18.5 cm
Package 2 Weight - 296.0 g
Unit Type of Package 3 - S03
Number of Units in Package 3 - 80
Package 3 Height - 30.0 cm
Package 3 Width - 30.0 cm
Package 3 Length - 40.0 cm
Package 3 Weight - 2.809 kg
Pret: 22,81 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-mecanism-1-pole-2-way-16ax-2-module-screw-terminals-vopsit-ip4x-aluminiu-319017>