

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER BUTON DUBLU, NEW UNICA, 1-POLE 1-WAY, 10AX, 2
 MODULE, TERMINAL FARA SURUBURI, VOPSIT, IP4X, ALB**

Schneider Electric New Unica switch NU321154 is a mechanism in color anthracite with 2 rockers. This is a double one-way switch. The device's fixing mode is clip-in. Its rated current is 10AX. It is 45 mm in width, 45 mm in height and 34.25 mm in depth with an embedding depth of 21.15 mm. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. This switch has screwless terminals connection terminals. Being made of Cu.Zn15, Cu.Zn37, PBT (polybutylene terephthalate) GF31, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized material, this skin is reliable and resistant. It obtained AENOR, CE, EAC, NF certificate. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica
 Product or component type - Switch
 device presentation - Mechanism
 Technology type - Electromechanical
 Switch function - 1-pole 1-way
 Number of rocker - 2
 Device application - Light control
 Provided equipment - Internal power connection
 Colour tint - Anthracite (RAL 7021)
 Type of packing - Flow-pack
 Complementary
 Rated current - 10 AX
 [Ue] rated operational voltage - 250 V
 Network type - AC
 Network frequency - 50/60 Hz
 Electrical durability - 20000 cycles, cos phi = 0.6
 Insulation resistance - > 5 MOhm at 500 V
 Dielectric strength - 2000 V
 Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3
 Condition of use - Indoor
 Opening distance - > 3 mm
 Actuator - Rocker
 Number of modules - 2 modules
 Connections - terminals - Screwless terminals
 Cable cross section - 0.5-2.5 mm² rigid cable
 0.5-2.5 mm² flexible cable
 Material - PBT (polybutylene terephthalate) GF31: release button
 CuZn15: internal link
 Thermoplastic ABS-UV stabilised: mechanism rocker
 PC (polycarbonate) GF10 FR: casing
 CuZn37: terminals
 Marking - Without marking
 Surface finish - Matt
 specific treatment - integrated within the material - Painted
 Fixing mode - Clip-in
 Width - 45 mm
 Height - 45 mm
 Depth - 34.25 mm
 Embedding depth - 21.15 mm
 Net weight - 0.0284 kg
 Ambient air temperature for operation - -5 to +40 A°C
 Ambient air temperature for storage - -5 to +50 A°C
 Standards - EN 60669-1
 LV directive
 EMC directive
 Product certifications - CE
 AENOR
 EAC
 NF
 Resistance to chemical agents - Resistant to alcohol (70 %)
 Resistant to alcohol (96 %)
 Resistant to A-Lactic Acid
 Resistant to diluted quaternary ammonium
 Resistant to diluted bleach
 Resistant to diluted ammonia
 Resistant to soapy water
 Resistant to crystal cleaner
 Resistant to hydrogen peroxide 10 volumes
 Resistant to hexane
 Environment
 IP degree of protection - IP4X
 IK degree of protection - IK04
 Environmental characteristic - Alcohol
 Window-cleaning fluid

Acetone
Petrol
UV resistant
Oil
Bleach
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 3.0 cm
Package 1 Width - 4.5 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 30.0 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 5.5 cm
Package 2 Width - 14.0 cm
Package 2 Length - 26.0 cm
Package 2 Weight - 373.0 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 240
Package 3 Height - 30.0 cm
Package 3 Width - 40.0 cm
Package 3 Length - 60.0 cm
Package 3 Weight - 9.583 kg
Pret: 34,11 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/buton-dublu-new-unica-1-pole-1-way-10ax-2-module-terminal-fara-suruburi-vopsit-ip4x-alb-319060>