

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTREERUPATOR, NEW UNICA, 1-POLE 2-WAY, 10AX, 2
 MODULE, TERMINAL FARA SURUBURI, IP4X, ALB**

Schneider Electric New Unica switch NU520318D is a mechanism with zamak fixing frame in color white. This is a 1-pole 2-way switch. The fixing mode of this device is screws or claws. Its rated current is 10AX. It is 74.5 mm in width, It is 74.5 mm in height, and 34.25 mm in depth with an embedding depth of 21.15 mm. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. Its connection terminals are screwless terminals. This switch is AENOR, CE, EAC, NF certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.

Main
 Range of product - New Unica
 Product or component type - Switch
 device presentation - Mechanism with fixing frame
 Technology type - Electromechanical
 Switch function - 1-pole 2-way
 Number of rocker - 1
 Device application - Light control
 Provided equipment - Fixing frame
 Colour tint - White (RAL 9003)
 Type of packing - Flow-pack
 Complementary
 Rated current - 10 AX
 [Ue] rated operational voltage - 250 V
 Network type - AC
 Network frequency - 50/60 Hz
 Electrical durability - 20000 cycles, cos phi = 0.6
 Insulation resistance - > 5 MOhm at 500 V
 Dielectric strength - 2000 V
 Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3
 Opening distance - > 3 mm
 Actuator - Rocker
 Number of modules - 2 modules
 Connections - terminals - Screwless terminals
 Cable cross section - 0.5-2.5 mm² rigid cable
 0.5-2.5 mm² flexible cable
 Material - Zamak: fixing frame
 Thermoplastic ABS-UV stabilised: mechanism rocker
 PC (polycarbonate) GF10 FR: casing
 CuZn37: terminals
 PBT (polybutylene terephthalate) GF30: release button
 Marking - Without marking
 Surface finish - Glossy
 Fixing mode - Screws or claws
 Width - 74.5 mm
 Height - 74.5 mm
 Depth - 34.25 mm
 Embedding depth - 21.15 mm
 Net weight - 0.0598 kg
 Ambient air temperature for operation - -5 to 40 A°C
 Ambient air temperature for storage - -5 to 50 A°C
 Standards - IEC 60669-1
 LV directive
 Product certifications - CE
 AENOR
 EAC
 NF
 VDE
 Resistance to chemical agents - Resistant to alcohol (70 %)
 Resistant to alcohol (96 %)
 Resistant to A-Lactic Acid
 Resistant to diluted quaternary ammonium
 Resistant to diluted bleach
 Resistant to diluted ammonia
 Resistant to soapy water
 Resistant to crystal cleaner
 Resistant to hydrogen peroxide 10 volumes
 Resistant to hexane
 Environment
 IP degree of protection - IP4X
 IK degree of protection - IK04
 Environmental characteristic - Oil
 UV resistant
 Acetone
 Liquid soap
 Window-cleaning fluid

Petrol
Alcohol
Bleach
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 3.5 cm
Package 1 Width - 7.5 cm
Package 1 Length - 7.5 cm
Package 1 Weight - 59.0 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 10.3 cm
Package 2 Width - 13.7 cm
Package 2 Length - 37.5 cm
Package 2 Weight - 681.0 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 100
Package 3 Height - 30.0 cm
Package 3 Width - 40.0 cm
Package 3 Length - 60.0 cm
Package 3 Weight - 7.513 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-1-pole-2-way-10ax-2-module-terminal-fara-suruburi-ip4x-alb-319062>