

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER INTREERUPATOR DUBLU, NEW UNICA, 10 A, CU STUDIO FRAME, ALB

Schneider Electric New Unica switch NU221118D is a complete mechanism in color white with 2 rockers. This is a double 1-way switch with a studio frame. The device's fixing mode is long claws. Its rated current is 10A. It is 85 mm in width, 80 mm in height 34 mm in depth with an embedding depth of 22 mm. It reaches IP20 degree of protection which is very high. Its connection terminals are screwless terminals. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch

device presentation - Complete product

Technology type - Electromechanical

Switch function - 1-pole 1-way

Number of rocker - 2

2

Device application - Light control

Provided equipment - Internal power connection

Colour tint - White (RAL 9003)

Type of packing - Flow-pack

Complementary

Rated current - 10 A

10 AX

[Ue] rated operational voltage - 250 V

250 V

Network type - AC

AC

Network frequency - 50/60 Hz

50/60 Hz

Electrical durability - 10000 cycles

20000 cycles, cos phi = 0.6

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3

Condition of use - Indoor

Opening distance - > 3 mm

Actuator - Rocker

Number of modules - 2 modules

Connections - terminals - Screwless terminals

Cable cross section - 0.5-2.5 mm² rigid cable

0.5-2.5 mm² flexible cable

Material - ASA + PC: cover frame

ABS (acrylonitrile butadiene-styrene): cover frame

ABS (acrylonitrile butadiene-styrene): mechanism cover

Surface finish - Glossy

specific treatment - integrated within the material - Untreated

Fixing mode - Long claws

Width - 85 mm

Height - 85 mm

Depth - 34.25 mm

Embedding depth - 21.15 mm

Net weight - 0.025 kg

Ambient air temperature for operation - -5 to +40 A°C

Ambient air temperature for storage - -5 to +50 A°C

Standards - EN 60669-1

LV directive

EMC directive

Product certifications - CE

AENOR

EAC

NF

VDE

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP4X

IK degree of protection - IK04

Environmental characteristic - UV resistant

Oil
Petrol
Liquid soap
Acetone
Window-cleaning fluid
Bleach
Alcohol
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 5 cm
Package 1 Width - 8.5 cm
Package 1 Length - 8.5 cm
Package 1 Weight - 79 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 12 cm
Package 2 Width - 17.5 cm
Package 2 Length - 26 cm
Package 2 Weight - 925 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 80
Package 3 Height - 30 cm
Package 3 Width - 40 cm
Package 3 Length - 60 cm
Package 3 Weight - 8.103 kg
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialeelectric.ro/interruptor-dublu-new-unica-10-a-cu-studio-frame-alb-319096>