

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTRERUPATOR, NEW UNICA, INTERMEDIATE, 10AX, 1  
MODULE, TERMINAL FARA SURUBURI, ANTIBACTERIAN, IP4X, ALB**

Main  
Range of product - New Unica  
Product or component type - Switch  
device presentation - Mechanism  
Technology type - Electromechanical  
Switch function - Intermediate  
Number of rocker - 1  
Device application - Light control  
Colour tint - White (RAL 9003)  
Type of packing - Flow-pack  
Complementary  
Rated current - 10 A  
10 AX  
[Ue] rated operational voltage - 250 V  
Network type - AC  
Network frequency - 50/60 Hz  
Electrical durability - 20000 cycles, cos phi = 0.6  
Insulation resistance - > 5 MOhm at 500 V  
Dielectric strength - 2000 V  
Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3  
Condition of use - Indoor  
Opening distance - > 3 mm  
Actuator - Rocker  
Number of modules - 1 module  
Connections - terminals - Screwless terminals  
Cable cross section - 0.5-2.5 mm<sup>2</sup>  
Marking - Without marking  
Surface finish - Glossy  
specific treatment - integrated within the material - Antibacterial  
Fixing mode - Clip-in  
Width - 22.5 mm  
Height - 45 mm  
Depth - 34.25 mm  
Embedding depth - 21.15 mm  
Net weight - 0.0192 kg  
Ambient air temperature for operation - -5 to +40 A°C  
Ambient air temperature for storage - -5 to +50 A°C  
Standards - EN 60669-1  
LV directive  
EMC directive  
Product certifications - CE  
AENOR  
EAC  
NF  
VDE  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IP degree of protection - IP4X  
IK degree of protection - IK04  
Environmental characteristic - Alcohol  
Window-cleaning fluid  
Acetone  
Petrol  
UV resistant  
Oil  
Bleach  
Liquid soap  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 2.3 cm  
Package 1 Width - 3.8 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 21.0 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 20  
Package 2 Height - 8.2 cm

Package 2 Width - 17.7 cm  
Package 2 Length - 18.5 cm  
Package 2 Weight - 504.0 g  
Unit Type of Package 3 - S02  
Number of Units in Package 3 - 40  
Package 3 Height - 15.0 cm  
Package 3 Width - 30.0 cm  
Package 3 Length - 40.0 cm  
Package 3 Weight - 1.323 kg

Pret: 24,41 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-intermediate-10ax-1-module-terminal-fara-suruburi-antibacterian-ip4x-alb-319141>