

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER BUTON JALUZELE, NEW UNICA, 10 AX, 250 V, AC, 1
 MODULE, ALB**

Schneider Electric New Unica switch NU310818SC is a mechanism in color white. This is a roller blind switch. Clip-in this rocker switch for the fixation. Its rated current is 10AX. It is 22.4 mm in width, It is 45 mm in height, and 33 mm in depth with an embedding depth of 21 mm. The IP rating of this device is IP20. Its connection terminals are screw terminals. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica
 Device application - Control
 Product or component type - Shutter control
 device presentation - Mechanism
 Rated current - 10 AX
 [Ue] rated operational voltage - 250 V
 Network type - AC
 Network frequency - 50/60 Hz
 Fixing mode - Clip-in
 Colour tint - White (RAL 9003)
 Complementary
 device mounting - Flush
 Number of modules - 1 module
 Technology type - Electromechanical
 Actuator - Rocker
 Number of rocker - 2
 Switch function - 1-pole 2-way
 Switch application - Roller blind
 Number of poles - 1
 Contacts type and composition - 1 C/O
 mechanical interlocking - Interlock between up/down
 [Iu] rated interrupted current - 2.5 A for motor
 Opening distance - > 3 mm
 Pilot light - Without LED
 Marking - Down
 UP
 Connections - terminals - Screw terminals
 Cable cross section - 2.5 mm² flexible cable
 1.5a€;2.5 mm² flexible cable
 2.5 mm² rigid cable
 1.5a€;2.5 mm² rigid cable
 Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3
 Electrical durability - 10000 cycles, cos phi = 0.6
 Insulation resistance - > 5 MOhm at 500 V
 Dielectric strength - 2000 V
 Material - ASA + PC: mechanism cover
 ABS (acrylonitrile butadiene-styrene): mechanism cover
 Standards - LV directive
 EMC directive
 EN 60669-1
 Product certifications - ISI
 CE
 Ambient air temperature for operation - -5a€;40 A°C
 Ambient air temperature for storage - -5a€;40 A°C
 Embedding depth - 31.5 mm
 Depth - 40.6 mm
 Width - 22.5 mm
 Height - 45 mm
 Net weight - 0.036 kg
 Environment
 IK degree of protection - IK04
 IP degree of protection - IP4X
 Environmental characteristic - Window-cleaning fluid
 Liquid soap
 Acetone
 UV resistant
 Oil
 Bleach
 Petrol
 Alcohol
 Packing Units
 Unit Type of Package 1 - PCE
 Number of Units in Package 1 - 1
 Package 1 Height - 4.05 cm
 Package 1 Width - 2.25 cm
 Package 1 Length - 4.5 cm
 Package 1 Weight - 21 g
 Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10
Package 2 Height - 6.5 cm
Package 2 Width - 12 cm
Package 2 Length - 18.5 cm
Package 2 Weight - 278.3 g
Unit Type of Package 3 - S04
Number of Units in Package 3 - 360
Package 3 Height - 30 cm
Package 3 Width - 40 cm
Package 3 Length - 60 cm
Package 3 Weight - 10.722 kg
Pret: 35,24 lei (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/buton-jaluzele-new-unica-10-ax-250-v-ac-1-module-alb-319153>