

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTERRUPATOR, NEW UNICA, 2-POLE 1-WAY, 16AX, 2
 MODULE, SCREW TERMINALS, VOPSIT, IP4X, ALUMINIU**

Schneider Electric New Unica switch NU526230 is a mechanism with zamak fixing frame in color aluminium. This is a 2-pole 1-way switch. The device's fixing mode is screws or claws. Its rated current is 16AX. It is 74.5 mm in width, It is 74.5 mm in height, and 37.75 mm in depth with an embedding depth of 24.65 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. Its connection terminals are screw terminals. Being made of Cu.Zn5 Ag, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized material, this skin is reliable and resistant. This switch is AENOR, CE, EAC, NF certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica
 Product or component type - Switch
 device presentation - Mechanism with fixing frame
 Technology type - Electromechanical
 Switch function - 2-pole 1-way
 Number of rocker - 1
 Device application - Light control
 Provided equipment - Fixing frame
 Colour tint - Aluminium
 Type of packing - Flow-pack
 Complementary
 Rated current - 16 AX
 [Ue] rated operational voltage - 250 V
 Network type - AC
 Network frequency - 50/60 Hz
 Electrical durability - 20000 cycles, cos phi = 0.6
 Insulation resistance - > 5 MOhm at 500 V
 Dielectric strength - 2000 V
 Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3
 Opening distance - > 3 mm
 Actuator - Rocker
 Number of modules - 2 modules
 Connections - terminals - Screw terminals
 Cable cross section - 0.4 mm² rigid cable
 0.4 mm² flexible cable
 Material - CuZn5 Ag; terminals
 Thermoplastic ABS-UV stabilised: mechanism rocker
 PC (polycarbonate) GF10 FR: casing
 Marking - 0 - 1
 Surface finish - Glossy
 specific treatment - integrated within the material - Painted
 Fixing mode - Screws or claws
 Width - 74.5 mm
 Height - 74.5 mm
 Depth - 37.75 mm
 Embedding depth - 24.65 mm
 Net weight - 0.0586 kg
 Ambient air temperature for operation - -5 to 40 A°C
 Ambient air temperature for storage - -5 to 50 A°C
 Standards - LV directive
 IEC 60669-1
 Product certifications - CE
 AENOR
 EAC
 NF
 VDE
 Resistance to chemical agents - Resistant to alcohol (70 %)
 Resistant to alcohol (96 %)
 Resistant to A-Lactic Acid
 Resistant to diluted quaternary ammonium
 Resistant to diluted bleach
 Resistant to diluted ammonia
 Resistant to soapy water
 Resistant to crystal cleaner
 Resistant to hydrogen peroxide 10 volumes
 Resistant to hexane
 Environment
 IP degree of protection - IP4X
 IK degree of protection - IK04
 Environmental characteristic - Oil
 UV resistant
 Acetone
 Liquid soap
 Window-cleaning fluid

Petrol
Alcohol
Bleach
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 7.5 cm
Package 1 Width - 7.5 cm
Package 1 Length - 3.8 cm
Package 1 Weight - 57 g
Unit Type of Package 2 - S02
Number of Units in Package 2 - 10
Package 2 Height - 15 cm
Package 2 Width - 30 cm
Package 2 Length - 40 cm
Package 2 Weight - 994 g
Unit Type of Package 3 - P06
Number of Units in Package 3 - 160
Package 3 Height - 77 cm
Package 3 Width - 80 cm
Package 3 Length - 60 cm
Package 3 Weight - 24404 g
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-2-pole-1-way-16ax-2-module-screw-terminals-vopsit-ip4x-aluminiu-319170>