


Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTERRUPATOR, NEW UNICA, 2-POLE 1-WAY, 16AX, 2
 MODULE, SCREW TERMINALS, NETRATAT, IP4X, BEJ**

Schneider Electric New Unica switch NU526244 is a mechanism with zamak fixing frame in color beige. This is a 2-pole 1-way switch. The fixing mode of this device is screws or claws. Its rated current is 16AX. It is 74.5 mm in width, It is 74.5 mm in height, 37.75 mm in depth with an embedding depth of 24.65 mm. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. Its connection terminals are screw terminals. Cu.Zn5 Ag, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized This switch is AENOR, CE, EAC, NF certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica

Product or component type - Switch
 device presentation - Mechanism with fixing frame

Technology type - Electromechanical

Switch function - 2-pole 1-way

Number of rocker - 1

Device application - Light control

Provided equipment - Fixing frame

Colour tint - Beige (RAL 1013)

Type of packing - Flow-pack

Complementary

Rated current - 16 AX

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Electrical durability - 20000 cycles, cos phi = 0.6

Insulation resistance - > 5 MOhm at 500 V

Dielectric strength - 2000 V

Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3

Opening distance - > 3 mm

Actuator - Rocker

Number of modules - 2 modules

Connections - terminals - Screw terminals

Cable cross section - 0.4 mm² rigid cable

0.4 mm² flexible cable

Material - CuZn5 Ag: terminals

Thermoplastic ABS-UV stabilised: mechanism rocker

PC (polycarbonate) GF10 FR: casing

Marking - 0 - 1

Surface finish - Glossy

specific treatment - integrated within the material - Untreated

Fixing mode - Screws or claws

Width - 74.5 mm

Height - 74.5 mm

Depth - 37.75 mm

Embedding depth - 24.65 mm

Net weight - 0.0586 kg

Ambient air temperature for operation - -5 to +40 A°C

Ambient air temperature for storage - -5 to +50 A°C

Standards - IEC 60669-1

LV directive

Product certifications - CE

AENOR

EAC

NF

VDE

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP4X

IK degree of protection - IK04

Environmental characteristic - Oil

UV resistant

Acetone

Liquid soap

Window-cleaning fluid

Petrol

Alcohol

Bleach

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 7.5 cm

Package 1 Width - 7.5 cm

Package 1 Length - 3.8 cm

Package 1 Weight - 57 g

Unit Type of Package 2 - CAR

Number of Units in Package 2 - 10

Package 2 Height - 8.2 cm

Package 2 Width - 19.7 cm

Package 2 Length - 22.6 cm

Package 2 Weight - 675 g

Unit Type of Package 3 - S03

Number of Units in Package 3 - 50

Package 3 Height - 30 cm

Package 3 Width - 30 cm

Package 3 Length - 40 cm

Package 3 Weight - 3813 g

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/interruptor-new-unica-2-pole-1-way-16ax-2-module-screw-terminals-netratat-ip4x-bej-319172>