

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410



**SCHNEIDER INTERRUPATOR, NEW UNICA, 2-POLE 1-WAY, 16AX, 2  
 MODULE, SCREW TERMINALS, VOPSIT, IP4X, ANTRACIT**

Schneider Electric New Unica switch NU526254 is a mechanism with zamak fixing frame in color anthracite. This is a 2-pole 1-way switch. The device's fixing mode is screws or claws. Its rated current is 16AX. It is 74.5 mm in width, 74.5 mm in height and 37.75 mm in depth with an embedding depth of 24.65 mm. The surface finish is painted powder coated. The IP rating of this device is IP21D which is very high. Its connection terminals are screw terminals. The switch is made of Cu.Zn5 Ag, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilized, making it resistant and durable. This switch is AENOR, CE, EAC, NF certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range of product - New Unica  
 Product or component type - Switch  
 device presentation - Mechanism with fixing frame  
 Technology type - Electromechanical  
 Switch function - 2-pole 1-way  
 Number of rocker - 1  
 Device application - Light control  
 Provided equipment - Fixing frame  
 Colour tint - Anthracite (RAL 7021)  
 Type of packing - Flow-pack  
 Complementary  
 Rated current - 16 AX  
 [Ue] rated operational voltage - 250 V  
 Network type - AC  
 Network frequency - 50/60 Hz  
 Electrical durability - 20000 cycles, cos phi = 0.6  
 Insulation resistance - > 5 MOhm at 500 V  
 Dielectric strength - 2000 V  
 Minimum load breaking capacity - 200 operations 1.25 In and 1.1 Un, cos phi = 0.3  
 Opening distance - > 3 mm  
 Actuator - Rocker  
 Number of modules - 2 modules  
 Connections - terminals - Screw terminals  
 Cable cross section - 0.4 mm<sup>2</sup> rigid cable  
 0.4 mm<sup>2</sup> flexible cable  
 Material - CuZn5 Ag: terminals  
 Thermoplastic ABS-UV stabilised: mechanism rocker  
 PC (polycarbonate) GF10 FR: casing  
 Marking - 0 - 1  
 Surface finish - Matt  
 specific treatment - integrated within the material - Painted  
 Fixing mode - Screws or claws  
 Width - 74.5 mm  
 Height - 74.5 mm  
 Depth - 37.75 mm  
 Embedding depth - 24.65 mm  
 Net weight - 0.0586 kg  
 Ambient air temperature for operation - -5 to +40 A°C  
 Ambient air temperature for storage - -5 to +50 A°C  
 Standards - IEC 60669-1  
 LV directive  
 Product certifications - CE  
 AENOR  
 EAC  
 NF  
 VDE  
 Resistance to chemical agents - Resistant to alcohol (70 %)  
 Resistant to alcohol (96 %)  
 Resistant to A-Lactic Acid  
 Resistant to diluted quaternary ammonium  
 Resistant to diluted bleach  
 Resistant to diluted ammonia  
 Resistant to soapy water  
 Resistant to crystal cleaner  
 Resistant to hydrogen peroxide 10 volumes  
 Resistant to hexane  
 Environment  
 IP degree of protection - IP4X  
 IK degree of protection - IK04  
 Environmental characteristic - Oil  
 UV resistant  
 Acetone  
 Liquid soap  
 Window-cleaning fluid  
 Petrol

Alcohol

Bleach

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 7.5 cm

Package 1 Width - 7.5 cm

Package 1 Length - 3.8 cm

Package 1 Weight - 57 g

Unit Type of Package 2 - S02

Number of Units in Package 2 - 10

Package 2 Height - 15 cm

Package 2 Width - 30 cm

Package 2 Length - 40 cm

Package 2 Weight - 994 g

Unit Type of Package 3 - P06

Number of Units in Package 3 - 160

Package 3 Height - 77 cm

Package 3 Width - 60 cm

Package 3 Length - 80 cm

Package 3 Weight - 24.404 kg

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-new-unica-2-pole-1-way-16ax-2-module-screw-terminals-vopsit-ip4x-antracit-319174>