



Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 (primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, İlfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410





Schneider Electric New Unica telephone socket NU349730 in color aluminium is a mechanism for data communication and with 2 modules. The telephone socket type is RJ12. Its matching mounting box can be recessed into the surface of the wall with flush type. It is 45 mm in width, 45 mm in height, and 34 mm in depth. Besides, the IP rating of this device is IP20. Being environmentally friendly, this telephone socket is a green premium product too. And it is mercury free as well as heavy metal free, taking care of the environment and your health all the time. The telephone socket is made of thermoplastic ABS-UV stabilised, making it as resistant as possible. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Telephone socket Device application - Communication device presentation - Mechanism

Colour tint - Aluminium Telephone socket type - RJ12 (6 contacts) - category 3 at 16 Mbit/s

Complementary Socket number - 1

Number of modules - 2 modules

Connections - terminals - Screw terminals twisted pair

device mounting - Flush Fixing mode - Clip-in

Material - Thermoplastic ABS-UV stabilised: central plate Depth - 34 mm Width - 45 mm Height - 45 mm

Embedding depth - 34 mm

Ambient air temperature for operation - -25a€¦55 A°C Ambient air temperature for storage - -25a€¦55 A°C

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium

Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IP degree of protection - IP20 IK degree of protection - IK01

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 3.4 cm Package 1 Width - 4.5 cm Package 1 Length - 4.5 cm

Package 1 Weight - 16 g Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10 Package 2 Height - 5.5 cm Package 2 Width - 14 cm

Package 2 Length - 26 cm Package 2 Weight - 160 g Unit Type of Package 3 - S03

Number of Units in Package 3 - 100

Package 3 Height - 30 cm Package 3 Width - 30 cm Package 3 Length - 40 cm Package 3 Weight - 2.038 kg Pret: 36,55 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/new-unica-priza-telefon-1-x-rj12-2-maluminiu-319183