

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



SCHNEIDER VARIATOR, NEW UNICA, CU RAMA FIXARE, ROTARY PUSH TYPE, BEJ

Schneider Electric New Unica dimmer NU551444 is a mechanism with fixing frame in color beige with 2 modules. 230V is the rated operational voltage. And the dimmer's associated fuse rating is 16. And the control type of this dimmer is local control, remote control by auxiliary push-button. Its protection type is automatic overload protection, overheating protection, short-circuit protection, taking care of your safety as much as possible. Its matching mounting box can be recessed into the surface of the wall with flush type. Its connection terminals are screw terminal. What's more, its directives are 2014/30/EU - electromagnetic compatibility, 2014/35/EU - low voltage directive. It is 74.5 mm in width, 74.5 mm in height, 47 mm in depth, and with an embedding depth of 29 mm. And the product weighs 0.129 kg. Besides, the IP rating of this device is IP20. It obtained CE, EAC, FIMKO, NEMKO, NF, SEMKO, VDE certificate as well. What's more, it well satisfied the standard of EN 300-328, EN 301-489-17, EN 60669-2-1, EN 60730-2-7. And it is mercury free As a green premium product, this device is environmentally friendly as well. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Product brand - Schneider Electric
 Range - New Unica
 Type number - NH3514
 Product or component type - Dimmer
 Complementary
 device presentation - Mechanism with fixing frame
 Device application - Light control
 Dimmer type - Universal
 Dimmer control - Rotary push type
 Load type - Incandescent lamp: 5...200 W at 230 V AC
 Halogen lamp: 5...150 W at 230 V AC
 LED lamp: 5...100 VA at 230 V AC (RC LED mode)
 LED lamp: 5...20 VA at 230 V AC (RL LED mode)
 LV halogen lamps: 5...150 VA at 12 V AC (electronic transformer)
 LV halogen lamps: 5...150 VA at 12 V AC (wound transformer)
 Function available - With memory function
 [Ue] rated operational voltage - 230 V AC 50 Hz
 Associated fuse rating - 16 A
 Protection type - Short-circuit protection
 Overheating protection
 Automatic overload protection
 colour - Beige (RAL 1013)
 Surface finish - Glossy
 Number of modules - 2 modules
 Number of outputs - 1
 Control type - Local control dimming up/down control
 Local control automatic load detection
 Remote control by auxiliary push-button
 Connected auxiliaries - Unlimited number of push-buttons, distance : 50 m
 Provided equipment - Fixing frame
 User manual
 Connections - terminals - Screw terminal
 Number of loop terminals - 2
 Clamping connection capacity - 1.5...2.5 mmA² for solid cable(s)
 1.5...2.5 mmA² for solid stranded cable(s)
 Shape of screw head - Pozidriv No 1 and combi
 Tightening torque - 0.5 N.m
 Material - PC (polycarbonate) GF10 FR: casing
 Metal: terminals
 Thermoplastic ABS-UV stabilised: central plate
 Zamak: fixing frame
 device mounting - Flush
 Fixing mode - By screws
 Type of installation - Indoor installation
 Quantity per set - 1 carton
 Embedding depth - 29 mm
 Depth - 47 mm
 Width - 74.5 mm
 Height - 74.5 mm
 Net weight - 0.129 kg
 Resistance to chemical agents - Resistant to alcohol (70 %)
 Resistant to alcohol (96 %)
 Resistant to A-Lactic Acid
 Resistant to diluted quaternary ammonium
 Resistant to diluted bleach
 Resistant to diluted ammonia
 Resistant to soapy water
 Resistant to crystal cleaner
 Resistant to hydrogen peroxide 10 volumes

Resistant to hexane
Environment
Ambient air temperature for operation - 5a€;40 A°C
Ambient air temperature for storage - 5a€;40 A°C
IP degree of protection - IP20
IK degree of protection - IK04
Environmental characteristic - UV resistant
Petrol
Window-cleaning fluid
Acetone
Bleach
Alcohol
Oil
Liquid soap
Standards - EN 60730-2-7
EN 301-489-17
EN 60669-2-1
EN 300-328
Directives - 2014/35/EU - low voltage directive
2014/30/EU - electromagnetic compatibility
Product certifications - NEMKO
EAC
VDE
FIMKO
CE
SEMKO
NF
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4.5 cm
Package 1 Width - 7.5 cm
Package 1 Length - 7.5 cm
Package 1 Weight - 80.5 g
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/variator-new-unica-cu-rama-fixare-rotary-push-type-bej-319204>