

Furnizor: **Sc Trivolt Distribution SRL**
 Reg. com.: J23/3300/2016
 CIF: RO36421140
 Adresa: Strada Apusului nr 3 (primul
 sens giratoriu Tehodor Pallady-
 Autostrada Soarelui), Catelu, Ilfov
 Banca: BRD
 IBAN: RO34BRDE441SV13182234410



SCHNEIDER NEW UNICA - LIGHT MODULE - 12...24 V AC - 2 MODULE

Schneider Electric New Unica light module NU3774 is a mechanism in color Its connection terminals are screw terminals. It is 22.5 mm in width, 45 mm in height, 31 mm in depth, with an embedding depth of 21 mm, And the product weighs 0.018 kg. With 1 module. The device's fixing mode is clip-in. In addition, the rated operational voltage of this device is 12...24V. Besides it is halogen free halogen free, which is good for your health. And it is mercury free as well as heavy metal free, taking care of the environment and your health all the time. Being made of PC (polycarbonate) GF10 FR material, this light module is quite reliable and resistant. The maximum input power of this light module is 0.2 W. Besides, it reaches IK03 protection level, which can help protect against impact. What's more, its directives are 2014/35/EU - low voltage directive. What's more, it well satisfied the standard of CE, EN 62094-1. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This light module is SVHC (substances of very high concern) free too. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main Range - New Unica

Product or component type - Light module
 device presentation - Mechanism
 [Ue] rated operational voltage - 12...24 V DC
 Number of modules - 1 module
 Fixing mode - Clip-in
 Colour tint - White
 Complementary
 Input power - 0.2 W
 Light block colour - White
 Bulb type - LED
 Connections - terminals - Screw terminals
 Clamping connection capacity - $\leq 2 \times 2.5 \text{ mm}^2$ for flexible cable(s)
 $\leq 2 \times 2.5 \text{ mm}^2$ for rigid cable(s)
 Material - PC: mechanism cover
 PC (polycarbonate) GF10 FR: casing
 Standards - EN 62094-1
 CE
 Directives - 2014/35/EU - low voltage directive
 Ambient air temperature for operation - $5\text{a}\text{€};45 \text{ A}^\circ\text{C}$
 Ambient air temperature for storage - $-5\text{a}\text{€};50 \text{ A}^\circ\text{C}$
 Embedding depth - 21 mm
 Depth - 31 mm
 Width - 22.5 mm
 Height - 45 mm
 Net weight - 0.018 kg
 Resistance to chemical agents - Resistant to alcohol (70 %)
 Resistant to alcohol (96 %)
 Resistant to A-Lactic Acid
 Resistant to diluted quaternary ammonium
 Resistant to diluted bleach
 Resistant to diluted ammonia
 Resistant to soapy water
 Resistant to crystal cleaner
 Resistant to hydrogen peroxide 10 volumes
 Resistant to hexane
 Environment
 IK degree of protection - IK03
 IP degree of protection - IP2xC
 Packing Units
 Unit Type of Package 1 - PCE
 Number of Units in Package 1 - 1
 Package 1 Height - 2.2 cm
 Package 1 Width - 4.5 cm
 Package 1 Length - 5.0 cm
 Package 1 Weight - 21.0 g
 Unit Type of Package 2 - BB1
 Number of Units in Package 2 - 10
 Package 2 Height - 8.0 cm
 Package 2 Width - 18.0 cm
 Package 2 Length - 25.0 cm
 Package 2 Weight - 320.0 g
 Unit Type of Package 3 - S03
 Number of Units in Package 3 - 60
 Package 3 Height - 30.0 cm
 Package 3 Width - 30.0 cm
 Package 3 Length - 40.0 cm
 Package 3 Weight - 2.36 kg
 Pret: 144,49 lei (TVA inclus)

