

Furnizor: **Sc Trivolt Distribution SRL**  
 Reg. com.: J23/3300/2016  
 CIF: RO36421140  
 Adresa: Strada Apusului nr 3 ( primul  
 sens giratoriu Tehodor Pallady-  
 Autostrada Soarelui), Catelu, Ilfov  
 Banca: BRD  
 IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER NEW UNICA - LIGHT MODULE CU INTRERUPATOR - 230 V AC - 2 MODULE**

Schneider Electric New Unica light module NU577744 is a mechanism with zamak fixing frame in color beige The connection terminals of this light module are screw terminals. It is 74.5 mm in width, 74.5 mm in height, 31 mm in depth, with an embedding depth of 21 mm, And the product weighs 0.068 kg. With 2 modules. The device's fixing mode is screws or claws. 230V is the rated operational voltage. Besides it is halogen free halogen free, which is good for your health. The light module is made of Cu. Zn37, PBT (polybutylene terephthalate) GF30, PC (polycarbonate) GF10 FR, thermoplastic ABS-UV stabilised, making it as resistant as possible. Besides, it reaches IK03 protection level, which can help protect against impact. What's more, its directives are 2014/35/EU - low voltage directive. What's more, it well satisfied the standard of CE, EN 62094-1. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Push-button + indicator  
 device presentation - Mechanism with fixing frame  
 [Ue] rated operational voltage - 230 V AC at 50...60 Hz

Number of modules - 2 modules

Fixing mode - Screws or claws

Colour tint - Beige

Complementary

Light block colour - White

Bulb type - LED

Connections - terminals - Screw terminals

Clamping connection capacity -  $\leq 2 \times 2.5 \text{ mm}^2$  for flexible cable(s)

$\leq 2 \times 2.5 \text{ mm}^2$  for rigid cable(s)

Material - PC: mechanism cover

PC (polycarbonate) GF10 FR: casing

Thermoplastic ABS-UV stabilised: rocker switch

CuZn37: terminals

PBT (polybutylene terephthalate) GF30: release button

PC (polycarbonate) GF10 FR: fixing frame

Standards - EN 62094-1

CE

Directives - 2014/35/EU - low voltage directive

Ambient air temperature for operation -  $5\text{a}\text{e}|45 \text{ A}^\circ\text{C}$

Ambient air temperature for storage -  $5\text{a}\text{e}|50 \text{ A}^\circ\text{C}$

Embedding depth - 21 mm

Depth - 31 mm

Width - 74.5 mm

Height - 74.5 mm

Net weight - 0.068 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK03

IP degree of protection - IP2xC

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 7.5 cm

Package 1 Width - 7.5 cm

Package 1 Length - 3.5 cm

Package 1 Weight - 68 g

Unit Type of Package 2 - CAR

Number of Units in Package 2 - 10

Package 2 Height - 8.2 cm

Package 2 Width - 19.7 cm

Package 2 Length - 22.6 cm

Package 2 Weight - 1605 g

Unit Type of Package 3 - S03

Number of Units in Package 3 - 50

Package 3 Height - 30 cm

Package 3 Width - 30 cm

Package 3 Length - 40 cm

Package 3 Weight - 8463 g  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-light-module-cu-intrerupator-230-v-ac-2-module-319239>