

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER PLACA ORNAMENT, UNICA STUDIO, PATRU MODULE, ALUMINIU**

Schneider Electric New Unica cover frame NU200830 is in color aluminium The cover frame is made of thermoplastic ABS-UV stabilised, making it as resistant as possible. This cover frame has 4 gangs Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Studio aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 298 mm in width. 85 mm in height. 10 mm in depth. Besides it is halogen free halogen free, which is good for your health. With 4 x 2 modules. The fixing mode of this device is clip-in. And the product weighs 0.042 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica a€" irresistible, beautiful, and innovative. Main

Range - New Unica  
Device application - Mounting  
Product or component type - Cover frame  
aesthetic name - Unica Studio  
Number of gangs - 4 gangs  
Installation direction - Horizontal/vertical  
Type of frame - Quadruple  
Number of modules - 4 x 2 modules  
Fixing mode - Clip-in  
Colour tint - Aluminium  
Complementary  
Material - Thermoplastic ABS-UV stabilised: cover frame  
Standards - IEC 60884-1  
IEC 60669-1  
Width - 298 mm  
Height - 85 mm  
Depth - 10 mm  
Net weight - 0.042 kg  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IK degree of protection - IK04  
IP degree of protection - IP21D  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 0.8 cm  
Package 1 Width - 8.5 cm  
Package 1 Length - 29.9 cm  
Package 1 Weight - 48 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 5  
Package 2 Height - 7.3 cm  
Package 2 Width - 9.5 cm  
Package 2 Length - 31.9 cm  
Package 2 Weight - 310 g  
Unit Type of Package 3 - S04  
Number of Units in Package 3 - 100  
Package 3 Height - 30 cm  
Package 3 Width - 40 cm  
Package 3 Length - 60 cm  
Package 3 Weight - 6.626 kg  
Pret: 39,71 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/placa-ornament-unica-studio-patru-module-aluminiu-319256>