

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER PLACA ORNAMENT, NEW UNICA, PATRU MODULE, ALB**

New Unica 4-gangs cover frame in color white. The cover frame is made of ASA + PC (polycarbonate), that provides enhanced heat resistance and enhances mechanical properties. It is environment-friendly, with UV resistant, acetone, alcohol, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. Simple and effective to install, mounting and fitting the cover frame to the device. This cover frame satisfies the EN 60669-1 standard. It is 298 mm in width, 80 mm in height 14 mm in depth. The device's fixing mode is clip-in. It reaches IP20 degree of protection which is very high. Besides, it reaches IK01 protection level, which can help protect against impact. This cover frame is SVHC (substances of very high concern) free. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers

requirements. Main

Range - New Unica

Device application - Mounting

Product or component type - Cover frame

aesthetic name - Unica Studio

Number of gangs - 4 gangs

Installation direction - Horizontal/vertical

Type of frame - Quadruple

Number of modules - 4 x 2 modules

Fixing mode - Screws

Colour tint - White (RAL 9003)

Complementary

Surface treatment - Untreated

Quantity per set - Set of 5

Standards - IEC 60669-1

IEC 60884-1

Width - 298 mm

Height - 85 mm

Depth - 10 mm

Net weight - 0.042 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 0.7 cm

Package 1 Width - 8.5 cm

Package 1 Length - 30 cm

Package 1 Weight - 43 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 5

Package 2 Height - 7.5 cm

Package 2 Width - 9.5 cm

Package 2 Length - 32.5 cm

Package 2 Weight - 291 g

Unit Type of Package 3 - S04

Number of Units in Package 3 - 100

Package 3 Height - 30 cm

Package 3 Width - 40 cm

Package 3 Length - 60 cm

Package 3 Weight - 6.459 kg

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/placa-ornament-new-unica-patru-module-alb-319409>