

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

SCHNEIDER PLACA ORNAMENT, UNICA STUDIO COLSAU, UN MODUL, GREY



This New Unica cover frame is in color light grey with 4 modules. Being made of ABS (acrylonitrile butadiene-styrene), ASA + PC material, this cover frame is quite reliable and resistant. It is environment-friendly, with UV resistant, acetone, alcohol, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. Simple and effective to install, mounting and fitting the cover frame to the device. It well satisfied the standard of EN 60669-1. It is 80 mm in width, 138 mm in height 13.7 mm in depth. The fixation for this cover frame is clip-in. It reaches IP20 degree of protection which is very high. It reaches IK01 protection level, which can help protect against impact. This cover frame is SVHC (substances of very high concern) free. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Mounting

Product or component type - Cover frame

aesthetic name - Unica Studio Color

Number of gangs - 1 gang

Installation direction - Horizontal

Type of frame - Single

Number of modules - 4 modules

Fixing mode - Screws

Colour tint - Light grey (Pantone 406C)

side color - White (RAL 9003)

Complementary

Material - Polycarbonate: intermediate plate

Surface treatment - Painted

Quantity per set - Set of 5

Standards - IEC 60669-1

IEC 60884-1

Width - 143 mm

Height - 85 mm

Depth - 10 mm

Net weight - 0.031 kg

Resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 1.1 cm

Package 1 Width - 8.5 cm

Package 1 Length - 14.25 cm

Package 1 Weight - 25 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 5

Package 2 Height - 6.5 cm

Package 2 Width - 12 cm

Package 2 Length - 18.5 cm

Package 2 Weight - 193.3 g

Unit Type of Package 3 - S03

Number of Units in Package 3 - 80

Package 3 Height - 30 cm

Package 3 Width - 30 cm

Package 3 Length - 40 cm

Package 3 Weight - 3.534 kg

Pret: 34,04 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/placa-ornament-unica-studio-colsau-un-modul-grey-319435>