

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER PLACA ORNAMENT, UNICA STUDIO METAL, DOUA MODULE, AURIU**

Schneider Electric New Unica cover frame NU280450 is in color bronze Being made of polycarbonate, thermoplastic ABS-UV stabilised material, this cover frame is quite reliable and resistant. This cover frame has 2 gangs Besides, it reaches IK04 protection level, which can help protect against impact. Also, it is environment-friendly, with UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid reached. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica Studio Metal aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 156 mm in width. 85 mm in height. 10 mm in depth. Besides it is halogen free halogen free, which is good for your health. With 2 x 2 modules. The fixing mode of this device is clip-in. And the product weighs 0.033 kg. New Unica features innovative functions to carry the range into the smart homes of the future. Welcome to the new Unica a€" irresistible, beautiful, and innovative. Main

Range - New Unica  
Device application - Mounting  
Product or component type - Cover frame  
aesthetic name - Unica Studio Metal  
Number of gangs - 2 gangs  
Installation direction - Horizontal/vertical  
Type of frame - Double  
Number of modules - 2 x 2 modules  
Fixing mode - Clip-in  
Colour tint - Bronze  
side color - White (RAL 9003)  
Complementary  
Material - Thermoplastic ABS-UV stabilised: cover frame  
Polycarbonate: intermediate plate  
Surface finish - Dotted finish  
Standards - IEC 60884-1  
IEC 60669-1  
Width - 156 mm  
Height - 85 mm  
Depth - 10 mm  
Net weight - 0.033 kg  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
IK degree of protection - IK04  
IP degree of protection - IP21D  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 1 cm  
Package 1 Width - 8.5 cm  
Package 1 Length - 15.6 cm  
Package 1 Weight - 33 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 3  
Package 2 Height - 6.5 cm  
Package 2 Width - 12.5 cm  
Package 2 Length - 18.5 cm  
Package 2 Weight - 164 g  
Unit Type of Package 3 - S04  
Number of Units in Package 3 - 108  
Package 3 Height - 30 cm  
Package 3 Width - 40 cm  
Package 3 Length - 60 cm  
Package 3 Weight - 6.618 kg  
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/placa-ornament-unica-studio-metal-doua-module-auriu-319588>