

Furnizor: **Sc Trivolt Distribution SRL** Reg. com.: J23/3300/2016 CIF: RO36421140

Adresa: Strada Apusului nr 3 ( primul sens giratoriu Tehodor Pallady-Autostrada Soarelui), Catelu, İlfov

Banca: BRD

IBAN: RO34BRDE441SV13182234410



## SCHNEIDER UNICA SYSTEM, COLOANAD, 2.15M, 4XDE SOUSBA/C2XC6ASTP-A/G

Schneider Electric Unica System+ pole INS45107 is a pre-wired, with outlets, cable and plug in color anthracite/grey. Being made of aluminium material, this pole is quite reliable and resistant. This is a free-standing and movable pole, double-sided. It comes pre-wired, each side configured with 4 x power outlets, side-earthed, USB type A and type C socket outlets, with cable, and 2 x Cat 6A S/FTP (Actassi) with cable. Including end piece with self-closing cable wrap and mounting instruction. The length of self-closing cable wrap is 2.0 m, the action radius 1.5 m from the connection point in the ceiling. This pole comes earthed. The foot can be ordered separately. The external cables cening. This pole colles earthed. The root can be of defed separately. The external cables are two unshielded  $3 \times 1.5 \text{ mm2}$  cable with side-earthed plug, 6.0 m total length, and two Cat 6A S/FTP (Actassi) data cables with RJ45 plugs, 10.0 m total length. This device is compatible with Unica outlet, Unica power supply. This product is sold in 1 piece. Unica System + a range of innovative and easy-to-install power supply and cable management solutions. Based on a contemporary design, that bring you flexibility, comfort, and a clutter-free working environment.Main

Range - Unica

Product type - Pole type of pole - Two-sided

Configuration - Pre-wired, with outlets, cable and plug

Outlet standard - Schuko Product compatibility - Unica outlet

Unica power supply Quantity package 1 / unit - 1

Complementary

Pole/post surface finish - Powder coated

Pole/post surface finish - Powder coated
Fixing mode - Free-standing
Number of power socket outlets - 4 at 250 V 16 A side earth
Integrated connection type - RJ45
USB type A, output voltage= 5 V DC at 2.4 A
USB type C, output voltage= 5 V DC at 2.4 A
Number of data socket outlets - 2 STP
Provided equipment - 2 x cable with 6 mm shielded cable cable
1 x cable with 10 mm unshielded cable cable

1 x cable with 10 mm unshielded cable cable

Clamping connection capacity - 3 x 1.5 mmA<sup>2</sup> Product material - Aluminium anthracite grey RAL 9010

Height - 2150 mm Width - 70 mm Depth - 70 mm Shape - I-shape Adjustment - Vertical: 2000 mm

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 20.0 cm Package 1 Width - 39.0 cm

Package 1 Length - 215.0 cm Package 1 Weight - 13.0 kg

Pret: 3 209,01 lei (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/unica-system-coloanad-2-15m-4xdesousba-c2xc6astp-a-g-319787