


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><u>LEDVANCE CORP DE ILUMINAT ETANS, LEDVANCE, 1200MM, 3960LM, IP66, 4000K, 33W</u></p> <p>Caracteristici generale Tip de sursa: LED neinlocuibil Echipat cu sursa: Da Durata nominala de viata (ore): 50000 h Grad de protectie (IP): IP66 Clasa de protectie la impact: IK08 Durata estimata de viata L80/B50 la 25 °C: 50000 Tip de conexiune: Conexiune cu surub</p> <p>Caracteristici materiale Material carcasa: Policarbonat Culoare carcasa: Alb</p> <p>Caracteristici tehnice iluminat Culoare lumina: Alb Indice de redare a culorilor (CRI Ra): 80 Indice de redare a culorilor (CRI): 80-89 Temperatura de culoare: 4000 K Plaja temperatura de culoare: 4000-4000 K Eficienta luminoasa: 123 Lm/W Flux luminos nominal conform IEC 62722-2-1: 3960 lm Tip de iluminat: Direct Unghiul de dispersie: Fascicul foarte larg >80° EN. Flickering value Pst LM: 1 Cod culoare lumina: 840 Fara functie de dimare: Da</p> <p>Caracteristici electrice Putere sistem: 33 W Tensiune alimentare: 220-240 V Tip alimentare: AC Clasa de protectie la atingere: II Frecventa retea: 50-60 Hz Factor de putere: 0.9 Intensitate curent nominala: 145 mA Tip de aparat: Droser electronic standard (HF) Echipament de control inclus: Nu Numar poli: 2</p> <p>Caracteristici de temperatura Temperatura ambientala: -20-45 °C</p> <p>Caracteristici montaj Poate fi montat aplicat: Da Poate fi montat pe plafon: Da Poate fi montat pe perete: Da</p> <p>Dimensiuni produs Latime: 60 mm Inaltime/adancime: 53 mm Lungime: 1243 mm</p> <p>Certificari Marcaj CE: Da Pret: 157,40 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/corp-de-iluminat-etans-ledvance-1200mm-3960lm-ip66-4000k-33w-343583</p>
---	--