


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410

	<p style="text-align: center;"><u>LEDVANCE CORP DE ILUMINAT ETANS, LEDVANCE, 1500MM, 6100LM, IP66, 4000K, 50W</u></p> <p>Caracteristici generale Tip de sursa: LED neinlocuibil Echipat cu sursa: Da Durata nominala de viata (ore): 50000 h Grad de protectie (IP): IP66 Clasa de protectie la impact: IK08 Tip de conexiune: Conexiune cu surub Caracteristici materiale Material carcasa: Policarbonat Culoare carcasa: Alb Caracteristici tehnice iluminat Culoare lumina: Alb Indice de redare a culorilor (CRI Ra): 80 Indice de redare a culorilor (CRI): 80-89 Temperatura de culoare: 4000 K Plaja temperatura de culoare: 4000-4000 K Eficienta luminoasa: 123 Lm/W Flux luminos nominal conform IEC 62722-2-1: 6100 lm Tip de iluminat: Direct Unghiul de dispersie: Fascicul foarte larg >80° EN. Flickering value Pst LM: 1 Cod culoare lumina: 840 Fara functie de dimare: Da Caracteristici electrice Putere sistem: 50 W Tensiune alimentare: 220-240 V Tip alimentare: AC Clasa de protectie la atingere: II Frecventa retea: 50-60 Hz Factor de putere: 0.9 Intensitate curent nominala: 228 mA Tip de aparat: Droser electronic standard (HF) Echipament de control inclus: Nu Numar poli: 2 Caracteristici de temperatura Temperatura ambientala: -20-45 °C Caracteristici montaj Poate fi montat aplicat: Da Poate fi montat pe plafon: Da Poate fi montat pe perete: Da Dimensiuni produs Latime: 60 mm Inaltime/adancime: 53 mm Lungime: 1543 mm Certificari Marcaj CE: Da Pret: 181,25 lei (TVA inclus)</p> <p>Detalii online: https://www.materialeelectrice.ro/corp-de-iluminat-etans-ledvance-1500mm-6100lm-ip66-4000k-50w-343588</p>
---	--