

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410

### **IEK HEAT-SHRINK CAP KTK35/15 35KW**



Used for sealing of ends of power cables with paper oil-impregnated insulation, plastic insulation and cross-linked polyethylene insulation, steel and polyethylene pipes. Inner surface of the cap is coated with adhesive thermomelting layer that ensures perfect sealing after shrinkage. The inner surface of the cap is coated with a layer of hot melt glue, which provides complete sealing of the cable ends after shrinkage. Caps are resistant to ultraviolet light and any weather conditions. The use of cable caps can significantly save time when preparing the cable for installation, eliminating the need to check the insulation for moisture. Caps can be used as plugs of steel and polymer pipes. Inner diameter before heat-shrink: 35

Type: EV004267  
Inner diameter after heat-shrink: 15  
Model: EV009930  
Shrink rate: EV009535  
Total length after shrink: 85  
Nominal cross section: -  
Operation temperature: -55...+125  
Colour: EV000206  
Material: EV000154  
Mounting temperature: -10...+50  
Tensile strength:  $\geq 13$   
Volumetric electrical resistance:  $\geq 1\tilde{N}...10^{16}$   
For dielectric strength up to:  $\geq 30$   
Min shrinkage start temperature: 110  
Min full shrinkage temperature: 150  
Thickness of adhesive layer after full thermus: 3,2  
Width of glue layer: 35  
Pret: 7,70 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/heat-shrink-cap-ktk35-15-35kw-310488>