

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHRACK CONECTOR IP20 RJ45G CAT.6A PT. AWG23

EAN-Code 9004840499025 Lungime 55,30mm Latime neta 13,80mm Temperatura minima a mediului ambient -10°C Inaltime 15,00mm Temperatura maxima a mediului ambient 60°C Masa neta 0,02kg. Standard ISO/IEC 11801, Category 6AANSI/TIA-568-C.2, Category 6A Electrical insulation resistance 500M Ω min. @100VDC Dielectric withstanding voltage 1000VDC or AC peak Contact to contact: 1500VDC 1500VDC or AC peak PoE 4PPoE (100W) Wire Gauge AWG26/7 - 23/7, AWG26/1 - 23/1 Cable routing straight (180°) Tip conexiune IDC terminal Housing Zinc-alloy fully shielded Pins Phosphor-bronze alloy, plated with 50I $\frac{1}{4}$ -inch Au IDC Phosphor-bronze alloy, plated with 100I $\frac{1}{4}$ -inch Sn Max. pulling force on the cable 50 Cicluri de conectare 750 Grad de protectie IP20 Impachetare Single packed in Polypack - assembly instructions included Accesorii Stecher pt. cabluri de instalatii
Pret: 44,31 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/conector-ip20-rj45g-cat-6a-pt-awg23-83728>