

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER SEPARATOR DE SARCINA COMPACT NSX400NA - 400 A - 3 POLI

range	ComPacT new generation	
product name	ComPacT NSX new generation	
product or component type	Switch disconnecter	
device short name	NSX400NA	
poles description	3P	
network type	AC	
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3	
[Ie] rated operational current	AC-22A: 400 A AC 50/60 Hz 220...690 V AC-23A: 400 A AC 50/60 Hz 220...690 V	
[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to IEC 60947-3	
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-3	
[Ith] conventional free air thermal current	400 A at 60 °C	
[Icm] rated short-circuit making capacity	330 kA with upstream protection circuit breaker 7.1 kA switch-disconnector alone	
breaking capacity code	NA	
suitability for isolation	Yes conforming to EN/IEC 60947-3	
contact position indicator	Yes	
visible break	No	
utilisation category	AC-22A AC-23A	
Complementary		
control type	Toggle	
mounting mode	Fixed	
mounting support	Backplate	
upside connection	Front	
downside connection	Front	
[Icw] rated short-time withstand current	1.93 kA during 20 s conforming to IEC 60947-3 5 kA during 1 s conforming to IEC 60947-3 5 kA during 3 s conforming to IEC 60947-3	
mechanical durability	15000 cycles conforming to IEC 60947-3	
electrical durability	AC-22A: 10000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-3 AC-22A: 2500 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-3 AC-22A: 5000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-3 AC-22A: 5000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-3 AC-23A: 10000 cycles 440 V AC 50/60 Hz In/2 conforming to IEC 60947-3 AC-23A: 2500 cycles 690 V AC 50/60 Hz In conforming to IEC 60947-3 AC-23A: 5000 cycles 440 V AC 50/60 Hz In conforming to IEC 60947-3 AC-23A: 5000 cycles 690 V AC 50/60 Hz In/2 conforming to IEC 60947-3	
connection pitch	45 mm	
height	255 mm	
width	140 mm	
depth	110 mm	

net weight	5.2 kg
compatibility code	NSX400
Environment	
standards	EN/IEC 60947 UL 508
product certifications	EAC CCC
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
electrical shock protection class	Class II
pollution degree	3 conforming to IEC 60664-1
ambient air temperature for operation	-25...70 °C
ambient air temperature for storage	-50...85 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.333 kg
Package 1 Height	15 cm
Package 1 width	16 cm
Package 1 Length	29.5 cm
Unit Type of Package 2	S04
Number of Units in Package 2	2
Package 2 Weight	11.369 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Pret: 2 472,99 lei (TVA inclus)	
Detalii online: https://www.materialelectrice.ro/separator-de-sarcina-compact-nsx400na-400-a-3-poli-97484	