

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER EASY UPS 3S 10 KVA 400 V 3:1 UPS FOR EXTERNAL BATTERIES**

Descriere High-efficiency 3-phase UPS that features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 10 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments. This UPS is supplied without batteries, so you can easily customize the battery solution.

Denumire model Easy UPS 3S 10 kVA 400 V 3:1 UPS for external batteries

Include Filtru de praf , Ghid de instalare

Capacitate putere de iesire 10.0 KW / 10.0 kVA

Putere max. configurabila (wati) 10.0 KW / 10.0 kVA

Tensiune nominala la iesire 230V

Distorsiune tensiune de iesire Sub 3%

Frecventa de iesire (sincronizata cu alimentarea de la retea) 50 Hz , 60 Hz

Alte tensiuni de iesire 220, 240V

Factor de varf 3 : 1

Online cu dubla conversie

Functionare la suprasarcina 150% for 1 minute 125% for 10 minutes

Tensiune nominala de intrare 400 3 Faz

Frecventa de intrare 45 - 65 Hz

Interval tensiune de intrare pentru operatii principale 304 - 477 V

Alte tensiuni la intrare 380 , 415

Curent maxim de intrare 18 A

Distorsiune armonica totala de intrare Less than 4% for full load

Tip de acumulator Nu se livreaza cu baterie interna. A se utiliza cu baterie interna terata

Port(uri) interfata E3S\_Parallel , E3S\_TempSensor

Inaltime maxima 530.0 mm

Latime maxima 250.0 mm

Adancime maxima 700.0 mm

Greutate neta 36.0 kg

Greutate de transport 50.0 kg

Inaltime transport 772.0 mm

Latime de transport 400.0 mm

Adancime transport 857.0 mm

Culoare Alb

Mediu de operare 0 - 40 °C

Umiditate relativa de functionare 0 - 95 (non-condensing) %

Inaltime de operare 0-984.3 metri

Temperatura de depozitare -15 - 40 °C

Umiditate relativa depozitare 0 - 95 (non-condensing) %

Inaltime depozitare 0-15000 metri

Zgomot sonor la 1 metru de suprafata unitatii 60.000 dB

Clasa de protectie IP 20

Aprobari reglementare CE , EAC , IEC 62040-1-1 , IEC 62040-2 , IEC 62040-3 , IEC

62040-4 , ISTA 2B , RCM , WEEE

Garantie standard 1 an reparatii sau inlocuire pe loc cu pornire autorizata din fabrica

RoHS (Restrictionarea substantelor periculoase) Conformitate

Regulament REACH REGULAMENT: Nu contine SVHC (Substante care prezinta motive

de ingrijorare deosebita)

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/easy-ups-3s-10-kva-400-v-3-1-ups-for-external-batteries-98136>