

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER EASY UPS 3S 10 KVA 400 V 3:3 UPS FOR EXTERNAL BATTERIES

Descriere High-efficiency 3-phase UPS that features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 10 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments. This UPS is supplied without batteries, so you can easily customize the battery solution.

Denumire model Easy UPS 3S 10 kVA 400 V 3:3 UPS for external batteries
Include Filtru de praf , Ghid de instalare

.....
Capacitate putere de iesire 10.0 KW / 10.0 kVA
Putere max. configurabila (wati) 10.0 KW / 10.0 kVA
Tensiune nominala la iesire 400 3 Faz
Distorsiune tensiune de iesire Sub 3%
Frecventa de iesire (sincronizata cu alimentarea de la retea) 50 Hz , 60 Hz
Alte tensiuni de iesire 380, 415V
Factor de varf 3 : 1
Online cu dubla conversie
Tensiune de iesire THD < 3% sarcina liniara
Functionare la suprasarcina 150% for 1 minute 125% for 10 minutes
Derivatie Bypass de intretinere incorporat
Tensiune nominala de intrare 400 3 Faz
Frecventa de intrare 45 - 65 Hz
Interval tensiune de intrare pentru operatii principale 304 - 477 V
Alte tensiuni la intrare 380 , 415
Curent maxim de intrare 18 A
Distorsiune armonica totala de intrare Sub 3% pentru capacitate maxima
Tip de acumulator Fara baterie interna - utilizeaza sistemul de baterie extern
Port(uri) interfata E3S_Parallel , E3S_TempSensor
Inaltime maxima 530.0 mm
Latime maxima 250.0 mm
Adancime maxima 700.0 mm
Greutate neta 36.0 kg
Greutate de transport 50.0 kg
Inaltime transport 772.0 mm
Latime de transport 400.0 mm
Adancime transport 700.0 mm
Culoare Alb
Mediu de operare 0 - 40 °C
Umiditate relativa de functionare 0 - 95 (non-condensing) %
Inaltime de operare 0-984.3 metri
Temperatura de depozitare -15 - 40 °C
Umiditate relativa depozitare 0 - 95 (non-condensing) %
Inaltime depozitare 0-14763.6 metri
Zgomot sonor la 1 metru de suprafata unitatii 60.000 dB
Pierdere termica online 516.000 BTU/h
Clasa de protectie IP 20
Aprobari reglementare CE , EAC , IEC 62040-1-1 , IEC 62040-2 , IEC 62040-3 , IEC 62040-4 , ISTA 2B , RCM , WEEE
Garantie standard 1 an reparatii sau inlocuire pe loc cu pornire autorizata din fabrica
Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/easy-ups-3s-10-kva-400-v-3-3-ups-for-external-batteries-98140>