

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER EASY UPS 3S 20 KVA 400 V 3:1 UPS WITH INTERNAL BATTERIES - 15 MINUTES RUNTIME**

Descriere High-efficiency 3-phase UPS with internal batteries providing a runtime of 15 minutes. The UPS features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 20 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments

Denumire model Easy UPS 3S 20 kVA 400 V 3:1 UPS with internal batteries - 15 minutes runtime

Include Filtru de praf , Ghid de instalare

Capacitate putere de iesire 20.0 KW / 20.0 kVA

Putere max. configurabila (wati) 20.0 KW / 20.0 kVA

Tensiune nominala la iesire 230V

Distorsiune tensiune de iesire Sub 3%

Frecventa de iesire (sincronizata cu alimentarea de la retea) 50 Hz , 60 Hz

Alte tensiuni de iesire 220, 240V

Factor de varf 3 : 1

Online cu dubla conversie

Toleranta tensiune de iesire +/- 1.5%

Tensiune de iesire THD Tensiune nominala de intrare 400 3 Faz

Frecventa de intrare 45 - 65 Hz

Interval tensiune de intrare pentru operatii principale 304 - 477 V

Alte tensiuni la intrare 380 , 415

Curent maxim de intrare 37 A

Distorsiune armonica totala de intrare Sub 5% pentru capacitate maxima

Tip de protectie necesara la intrare Circuit breaker and fuse

Tip de acumulator VRLA

Module baterie incluse 2

Battery Slots Empty 1

Nota suport baterie de schimb UPS weight does not include battery weight.

Tensiune nominala baterie 240 V

Terminare descarcare tensiune baterie +/-198 VDC

Terminare descarcare curent maxim baterie 54 A

Port(uri) interfata E3S Paralel , E3S\_TempSensor

Inaltime maxima 1400.0 mm

Latime maxima 380.0 mm

Adancime maxima 907.0 mm

Greutate neta 177.0 kg

Greutate de transport 186.0 kg

Inaltime transport 1640.0 mm

Latime de transport 563.0 mm

Adancime transport 1014.0 mm

Culoare Alb

Mediu de operare 0 - 40 °C

Umiditate relativa de functionare 0 - 95 (non-condensing) %

Inaltime de operare 0-984.3 metri

Temperatura de depozitare -15 - 40 °C

Umiditate relativa depozitare 0 - 95 (non-condensing) %

Inaltime depozitare 0-15000 metri

Zgomot sonor la 1 metru de suprafata unitatii 60.000 dB

Pierdere termica online 870.000 BTU/h

Clasa de protectie IP 20

Aprobari reglementare CE , EAC , IEC 62040-1-1 , IEC 62040-2 , IEC 62040-3 , IEC

62040-4 , ISTA 2B , RCM , WEEE

Garantie standard 1 an reparatii sau inlocuire pe loc cu pornire autorizata din fabrica

RoHS (Restrictionarea substantelor periculoase) Conformitate

Regulament REACH REGULAMENT: Nu contine SVHC (Substante care prezinta motive de ingrijorare deosebita)

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/easy-ups-3s-20-kva-400-v-3-1-ups-with-internal-batteries-15-minutes-runtime-98154>