


Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER EASY UPS 3S 20 KVA 400 V 3:3 UPS FOR EXTERNAL BATTERIES

Descriere High-efficiency 3-phase UPS that features advanced product features, competitive specifications, and robust electrical design, making business continuity easy in the data center or electrical room. This is an exceptionally easy to install, operate, maintain, and service 20 kVA UPS, ideal for small and medium businesses. Includes dust filter and conformance-coated boards for harsh environments. This UPS is supplied without batteries, so you can easily customize the battery solution.

Denumire model Easy UPS 3S 20 kVA 400 V 3:3 UPS for external batteries

Include Filtru de praf , Ghid de instalare

Capacitate putere de iesire 20.0 KW / 20.0 kVA

Putere max. configurabila (wati) 20.0 KW / 20.0 kVA

Tensiune nominala la iesire 400 3 Faz

Distorsiune tensiune de iesire Sub 3%

Frecventa de iesire (sincronizata cu alimentarea de la retea) 50 Hz , 60 Hz

Alte tensiuni de iesire 380, 415V

Factor de varf 3 : 1

Online cu dubla conversie

Tensiune de iesire THD < 3% sarcina liniara

Functionare la suprasarcina 150% for 1 minute 125% for 10 minutes

Derivatie Bypass de intretinere incorporat

Tensiune nominala de intrare 400 3 Faz

Frecventa de intrare 45 - 65 Hz

Interval tensiune de intrare pentru operatii principale 304 - 477 V

Alte tensiuni la intrare 380 , 415

Curent maxim de intrare 37 A

Tip de acumulator Fara baterie interna - utilizeaza sistemul de baterie extern

Port(uri) interfata E3S Parallel , E3S_TempSensor

Inaltime maxima 770.0 mm

Latime maxima 250.0 mm

Adancime maxima 800.0 mm

Greutate neta 58.0 kg

Greutate de transport 75.0 kg

Inaltime transport 1015.0 mm

Latime de transport 400.0 mm

Adancime transport 982.0 mm

Culoare Alb

Mediu de operare 0 - 40 °C

Umiditate relativa de functionare 0 - 95 (non-condensing) %

Inaltime de operare 0-984.3 metri

Temperatura de depozitare -15 - 40 °C

Umiditate relativa depozitare 0 - 95 (non-condensing) %

Inaltime depozitare 0-14763.6 metri

Zgomot sonor la 1 metru de suprafata unitatii 60.000 dB

Pierdere termica online 900.000 BTU/h

Clasa de protectie IP 20

Aprobari reglementare CE , EAC , IEC 62040-1-1 , IEC 62040-2 , IEC 62040-3 , IEC

62040-4 , ISTA 2B , RCM , WEEE

Garantie standard 1 an reparatii sau inlocuire pe loc cu pornire autorizata din fabrica

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/easy-ups-3s-20-kva-400-v-3-3-ups-for-external-batteries-98156>