

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER ACOS-B3UTRY

Descriere Highly efficient, easy-to-deploy 100kW, 400V 3-phase uninterruptible power supply (UPS) that brings best-in-class power protection to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Compact design, high-density technology and modular architecture keep total cost of ownership low and operational efficiency at the highest levels. Galaxy VS reduces your energy losses by up to 66% with the patented ECOConversion mode - reaching up to 99% efficiency levels and delivering more energy savings than even our industry-leading 97% efficiency in normal operating mode. The UPS is EcoStruxure-ready to give you peace of mind with cloud-based remote monitoring and management via your smartphone.

Includes 5x8 start-up service.

Denumire model ACOS-B3UTRY

Include Filtru de praf , Ghid de instalare , Gestionare integrata a retelei , Module de putere livrate cu instalare , Serviciu de pornire , Intrarea superioara si inferioara a cablului

Timp de livrare standard Se livreaza, de regula, in 2 saptamani

Toleranta tensiune de derivatie +/-10%

Curent maxim de intrare in derivatie 161 A

Capacitate putere de iesire 100.0 KW / 100.0 kVA

Putere max. configurabila (wati) 100.0 KW / 100.0 kVA

Tensiune nominala la iesire 400 3 Faz

Distorsiune tensiune de iesire Sub 3%

Frecventa de iesire (sincronizata cu alimentarea de la retea) 50 Hz , 60 Hz

Alte tensiuni de iesire 380, 415V

Factor de varf 2.5

Online cu dubla conversie

Tip forma de unda Unda sinusoidala

Conexiuni de iesire (1) Hard Wire 5-wire (3PH + N + G) (Battery Backup)

Toleranta tensiune de iesire +/-1% after 50ms

Tensiune de iesire THD _1% linear load and _3% non-linear load

Functionare la suprasarcina 150% for 1 minute 125% for 10 minutes

Derivatie Bypass static incorporat

Tensiune nominala de intrare 400 3 Faz

Frecventa de intrare 40 - 70 Hz

Conexiuni de intrare Cablu rigid 4 fire (3 Faz + G) , Cablu rigid 5 fire (3 Faz + N + G)

Interval tensiune de intrare pentru operatii principale 340 - 460 (400 V) V

Alte tensiuni la intrare 380 , 415

Curent maxim de intrare 182 A

Rezistenta maxima la scurtcircuit (Icw) 65.0

Distorsiune armonica totala de intrare Sub 3% pentru capacitate maxima

Tip de acumulator Fara baterie interna - utilizeaza sistemul de baterie extern

Tensiune nominala baterie 480-576VDC

Terminare descarcare tensiune baterie 384 Vdc

Terminare descarcare curent maxim baterie 271 A

Port(uri) interfata GVS_Parallel , GVS_WideUPSMB_C , SeismicKit ,

GVS_WideUPS_AirFilter

Calitate interfata SmartSlot™ disponibila 1

Panou de cda Interfata utilizator cu ecran tactil LCD

Alarma sonora Alarme sonore si vizibile prioritizate dupa gravitate

Inaltime maxima 1485.0 mm

Latime maxima 521.0 mm

Adancime maxima 847.0 mm

Greutate neta 250.0 kg

Greutate de transport 275.0 kg

Inaltime transport 1680.0 mm

Latime de transport 640.0 mm

Adancime transport 990.0 mm

Culoare Gloss level 85% , RAL 9003

Mediu de operare 0 - 40 °C

Umiditate relativa de functionare 0 - 95 (non-condensing) %

Inaltime de operare 0-984.3 metri

Temperatura de depozitare -25 to 55 °C

Umiditate relativa depozitare 10 - 80 (non-condensing) %

Inaltime depozitare 0-15000 metri

Zgomot sonor la 1 metru de suprafata unitatii 65.000 dB

Pierdere termica online 9499.400 BTU/h

Clasa de protectie IP 21

Aprobari reglementare CSA C22.2 NO. 107.3 , EN/IEC 62040-1 , EN/IEC 62040-2 ,

EN/IEC 62040-3 , FCC Partea 15 Clasa A , IEC 60721-4-2 Level 2M2 , UL 1778 5th

edition

Garantie standard 1 an reparatii sau inlocuire pe loc cu pornire autorizata din fabrica

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/acos-b3utry-98552>