

Furnizor: **Sc Trivolt Distribution SRL**  
Reg. com.: J23/3300/2016  
CIF: RO36421140  
Adresa: Strada Apusului nr 3 ( primul  
sens giratoriu Tehodor Pallady-  
Autostrada Soarelui), Catelu, Ilfov  
Banca: BRD  
IBAN: RO34BRDE441SV13182234410



### **SCHNEIDER GALAXY VS UPS 30KW 400V, 2 INTERNAL 9AH SMART MODULAR BATTERY STRINGS, EXPANDABLE TO 4, START-UP 5X8**

Descriere Highly efficient, easy-to-deploy 30kW, 400V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service and 2 smart high-capacity modular battery strings, expandable to 4 strings for extended runtime. Runtime charts available in the Documents tab.

Denumire model Galaxy VS UPS 30kW 400V, 2 internal 9Ah smart modular battery strings, expandable to 4, Start-up 5x8

Include Module de baterii livrare cu instalare , Filtru de praf , EcoStruxure Ready ((UPS)) , Ghid de instalare , Gestionare integrata a retelei , Module de putere livrare cu instalare , Serviciu de pornire

Timp de livrare standard Se livreaza, de regula, in 2 saptamani

Capacitate putere de iesire 30.0 KW / 30.0 kVA

Putere max. configurabila (wati) 30.0 KW / 30.0 kVA

Tensiune nominala la iesire 400 3 Faz

Distorsiune tensiune de iesire Sub 5%

Frecventa de iesire (sincronizata cu alimentarea de la retea) 50 Hz , 60 Hz

Factor de varf 2.5

Online cu dubla conversie

Tip forma de unda Unda sinusoidala

Conexiuni de iesire (1) Hard Wire 5-wire (3PH + N + G) (Battery Backup)

Toleranta tensiune de iesire +/-1% after 50ms

Functionare la suprasarcina 150% for 1 minute 125% for 10 minutes

Derivatie Bypass static incorporat

Tensiune nominala de intrare 400 3 Faz

Frecventa de intrare 40 - 70 Hz

Conexiuni de intrare Cablu rigid 3 cu fire (3 Faz + M) , Cablu rigid 5 fire (3 Faz + N + G)

Interval tensiune de intrare pentru operatii principale 340 - 460 (400 V) V

Alte tensiuni la intrare 380 , 415

Curent maxim de intrare 54 A

Rezistenta maxima la scurtcircuit (Icw) 65.0

Distorsiune armonica totala de intrare Sub 3% pentru capacitate maxima

Tip de acumulator VRLA

Tensiune nominala baterie 480 V

Terminare descarcare tensiune baterie 384 Vdc

Terminare descarcare curent maxim baterie 81 A

Port(uri) interfata GVS Parallel , GVS\_WideUPSMB\_C SeismicKit ,

GVS\_WideUPS\_AirFilter

Calitate interfata SmartSlot™ disponibila 1

Panou de cda Interfata utilizator cu ecran tactil LCD

Alarma sonora Alarme sonore si vizibile prioritizate dupa gravitate

Inaltime maxima 1485.0 mm

Latime maxima 521.0 mm

Adancime maxima 847.0 mm

Greutate neta 460.0 kg

Greutate de transport 490.0 kg

Inaltime transport 1680.0 mm

Latime de transport 640.0 mm

Adancime transport 990.0 mm

Culoare Gloss level 85% , RAL 9003 , Alb

Mediu de operare 0 - 40 °C

Umiditate relativa de functionare 0 - 95 (non-condensing) %

Inaltime de operare 0-984.3 metri

Temperatura de depozitare -15 - 40 °C

Umiditate relativa depozitare 0 - 95 (non-condensing) %

Inaltime depozitare 0-3000 metri

Zgomot sonor la 1 metru de suprafata unitatii 61.000 dB

Pierdere termica online 3395.000 BTU/h

Clasa de protectie IP 20

Aprobari reglementare CSA C22.2 NO. 107.3 , EN/IEC 62040-1 , EN/IEC 62040-2 ,

EN/IEC 62040-3 , IEC 60721-4-2 Level 2M2 , UL 1778 5th edition

Garantie standard 1 an reparatii sau inlocuire pe loc cu pornire autorizata din fabrica

Pret: 0,00 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/galaxy-vs-ups-30kw-400v-2-internal-9ah-smart-modular-battery-strings-expandable-to-4-start-up-5x8-98555>