

Furnizor: **Sc Trivolt Distribution SRL**
Reg. com.: J23/3300/2016
CIF: RO36421140
Adresa: Strada Apusului nr 3 (primul
sens giratoriu Tehodor Pallady-
Autostrada Soarelui), Catelu, Ilfov
Banca: BRD
IBAN: RO34BRDE441SV13182234410



SCHNEIDER COMUTATOR TEMPORAL MECANIC IH - PERIOADA CICLU 24 ORE SI 7 ZILE - 2 OC

range of product Acti 9
nume produs Acti 9 IH
nume scurt al dispozitivului IH
tip produs sau componenta Temporizator mecanic
numar de canale 2
functie disponibila Comutator manual de timp
domeniul de aplicare al aparatului Building
tip de sarcina 1 tub fluorescent compensat paralel, ballast : conventional (58 W) - 10 tub
fluorescent necorectat, ballast : conventional (58 W) - 10 tuburi fluorescente compensate
sel, ballast : conventional (58 W) - 15 tub fluorescent necorectat, ballast : conventional
(40 W) - 15 tuburi fluorescente compensate sel, ballast : conventional (40 W) - 2 tub
fluorescent compensat paralel, ballast : conventional (40 W) - lampa cu halogen 230 V
c.a. (1100 W) - lampa cu incandescenta 230 V c.a. (1100 W) - 3 tub fluorescent in montaj
dual, ballast : conventional (2 x 100 W) - 5 tub fluorescent in montaj dual, ballast :
conventional (2 x 58 W) - 6 tub fluorescent necorectat, ballast : conventional (100 W) - 6
tuburi fluorescente compensate sel, ballast : conventional (100 W)
durata ciclu 24 hours + 7 days
precizie de masurare +/- 1 s/zi
numar maxim de comutari 16 active - 16 inactive + 7 active - 7 inactive
durata interval minima 45 min + 12 h
tip de setare Manual time changeover
precizie de masurare +/- 1 s/zi 20 °C
putere consumata 2,5 VA
curent maxim de comutatie 16 A - 250 V c.a. pf = 1 - 4 A - 250 V c.a. pf = 0,6
[Ue] tensiune operationala nominala 230 V c.a. - 15...10 % la 50 Hz
durata de viata baterie 6 yr
timp rezerva Salvare program si timp 150 h
suport de montare Sina DIN
module de 9 mm 6
tenta de culoare Alb (RAL 9003)
conexiuni - borne Borne cu suruburi
grad de protectie IP IP20 B
latime 54 mm
inaltime 82 mm
adancime 66 mm
greutate produs 0,223 kg
temperatura ambianta pentru utilizare -20...55 °C
grad de protectie IP Borne IP20 B
Stare oferta sustenabila Produs Green Premium
Regulamentul REACH Declaratia REACH
Conform REACH fara SVHC Da
Directiva RoHS UE Conform Declaratia RoHS UE
Fara mercur Da
Informatii privind scutirea de la RoHS Da
Regulamentul RoHS Declaratia RoHS Produs in afara domeniului de aplicare a RoHS .
Declaratia privind substantele in scop informativ.
Raport de mediu Profilul ambiental al produsului
Profil circularitate Informatii privind sfarsitul duratei de viata
Garantie 18 luni
Pret: 505,16 lei (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/comutator-temporal-mecanic-ih-perioada-ciclu-24-ore-si-7-zile-2-oc-99833>