



SCHNEIDER EASYLOGIC PM2200 - CONTOR PUTERE&ENERG - PANA LA 15TH H - LCD - RS485 - CLASA 1

gama EasyLogic

nume produs EasyLogic PM2200

nume scurt al dispozitivului PM2200

tip produs sau componenta Power meter

domeniul de aplicare al aparatului Power monitoring - Sub billing

power quality analysis total harmonic distortion - up to the 15th harmonic

tip de masurare Apparent power min/max, total - Active and reactive power min/max, total - Current

min/max, avg - Tensiune min/max, avg - Frecventa min/max, avg - Distorsiune armonica de curent totala

THD (I) per phase - Distorsiune armonica de tensiune totala THD (U) per phase - Factor de putere min/max,

avg - Apparent energy total - Active and reactive energy total

metering type Active, reactive, apparent energy (signed, four quadrant) - Current I, I1, I2, I3 - Peak demand

currents - Peak demand power PM, QM, SM - Unbalance current - Active power P, P1, P2, P3 - Reactive

power Q, Q1, Q2, Q3 - Demand power P, Q, S - Voltage U, U21, U32, U13, V, V1, V2, V3 - Apparent

power S, S1, S2, S3 - Calculated neutral current

clasa de precizie Clasa 1 energie activa conformitate cu IEC 62053-21 - Clasa 1 energie reactiva conformitate cu IEC 62053-24 - Class 5 harmonic distortion (I THD & U THD)

precizie de masurare Apparent power +/- 1 % - Energie activa +/- 1 % - Energie reactiva +/- 1 % - Putere activa +/- 1 % - Tensiune +/- 0.5 % - Factor de putere +/- 0.01 - Curent +/- 0.5 % - Frecventa +/- 0.05 % curentul de masura 5...6000 mA

masurarea tensiunii 35...480 V c.a. 50/60 Hz between phases - 20...277 V c.a. 50/60 Hz between phase and neutral - 480...999000 V c.a. 50/60 Hz cu trafo de tensiune externe

gama de masurare a frecventei 45...65 Hz

[Us] tensiune nominala de alimentare 44...277 V c.a. 45...65 Hz +/- 10 % - 44...277 V c.c. +/- 10 %

frecventa retea 50 Hz - 60 Hz

semnalizare locala 100 ms 120 V c.a. tipic - 400 ms 230 V c.a. tipic - 50 ms 125 V c.c. tipic

[In] curent nominal 1 A - 5 A

maximum power consumption in VA 6 VA la 277 V c.a.

maximum power consumption in W 3,3 W (alimentare (c.a.)) - 2 W la 277 V (alimentare (c.c.))

input impedance current 5 MOhm

securizare a setarilor Protected by access code

tip afisaj LCD retro-iluminat

culoare afisaj Monochrome

rezolutie afisaj 129 x 128 pixeli

Demand intervals Configurable from 1 to 60 min

informatii afisate Demand current (past value) - Demand current (present value) - Demand power (past value) - Demand power (present value) - Voltage - Current - Frequency - Energy consumption - Harmonic distortion - Power factor - Active power - Apparent power - Reactive power - Unbalanced in % - Harmonic amplitude

tip de control 4 x buton

semnalizare locala Rosu LED output signal 1...9999000 pulse/ k_h (kWh, kVAh, kVARh) - Verde LED

module operation and integrated communication

numar de intrari 2 pulse

numar de iesiri 0

protocol port de comunicare Modbus RTU la 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps even/odd or none - 2 fire, izolatie 2500 V

suport pentru port de comunicatie Borna cu ?urub RS485

Inregistrare data Marcaj temporal - Min/max for 8 parameters

functie disponibila Real time clock

sampling rate 64 samples/cycle

cybersecurity Enable/disable communication ports

serviciu de comunicare Remote monitoring

limba Spaniola - - Engleza - Russian - Portugheza - Germana - Chinese

certificari produs CE conformitate cu IEC 61010-1 - CULus conformitate cu UL 61010-1 - CULus

conformitate cu CSA C22.2 No 61010-1 - RCM - EAC - C-Tick

mod de montare Clipsabil

pozitie de montare Vertical

suport de montare Framework

echipament livrat 1 x installation guide

measurement category Category III 480 V - Category II 480...600 V

clasa de izolatie electrica Izolatie dubla - Clasa II

Intarziere flacara V-0 conformitate cu UL 94

conexiuni - borne Transformator de curent screw connection (partea inferioara) 6 - Voltage inputs screw connection (sus) 4

material Polycarbonat

latime 96 mm

adancime Total 76,09 mm - Embedded 61,64 mm

inaltime 96 mm

greutate produs 300 g

Cod compatibilitate PM2220

durata de serviciu 7 yr

grad de protectie IP Fata IP54 conformitate cu SR EN 60529 - Body IP30 conformitate cu SR EN 60529

umiditate relativa 5...95 % la 50 °C

grad de poluare 2

temperatura de utilizare -10...60 °C

temperatura de depozitare -25...70 °C

alitudine de functionare Regulamentul REACH Declaratia REACH

Conform REACH fara SVHC Da

Directiva RoHS UE Under investigation

Fara mercur Da

Informatii privind scutirea de la RoHS Da

Regulamentul RoHS Declaratia RoHS

WEEE In Uniunea Europeana, produsele trebuie reciclate respectand sistemul specific de colectare a deseurilor si nu trebuie sa ajunga in pubelele de colectare a deseurilor menajere.

Garantie 18 luni

Pret: 1.596,02 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/easylogic-pm2220-contor-putere-energ-pana-la-15th-h-lcd-rs485-clasa-1-102275>