



## CAVI CABLU NHXH CU INTARZIERE LA FOC , FARA HALOGENURI 3X6

Cablu din cupru cu izolatie rezistenta la foc, fara halogenuri (Halogen Free) .

Caracteristici :

Emisie redusa de fum, fara gaze otravitoare

Bazat pe standarde: VDE 0276-604/VDE 0266 HD 604 S1

Rezistenta la foc 180 minute . Rezistenta in flacara 90 minute.

Temperatura de lucra -40°C.....+ 90°C

Tensiune 0,6-1KV

1. FLAME RETARDANT	IEC 60332-1-2;VDE 0482-332-1-2 EN 60332-1-2/BS EN 60332-1-2
2. FLAME PROPAGATION	IEC 60332-3-24/ VDE 0482-332-3-24 EN 60332 -3-24 BS EN 60332-3-24
3. SMOKE DENSITY	IEC 61034-2 VDE 0482-267-2-3 EN 61034-2/BS-EN 61034-2
4. CORROSIVE GAS TEST	IEC 60754-2;VDE 0482-267-2-3 EN 50267-2-3/BS EN 50267-2-3
5. HALOGEN-FREE TEST	IEC 60754-1;VDE 0482-267-2-1 EN 50267-2-1/BS EN 50267-2-1
6. CIRCUIT INTEGRITY(FE 180)	IEC 60331-21

7. CIRCUIT INTEGRITY WITH SHOCK IEC 6033-31/EN 50363 BS EN 50362 /VDE 0482-362

8. SYSTEM CIRCUIT INTEGRITY DIN 4102-12(E90)

Pret: 20,54 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/cablu-nhxx-cu-intarziere-la-foc-fara-halogenuri-3x6-11184>