

Image not found or type unknown



LOVATO DESCARCATOR TIP 2 PENTRU APLICATII FOTOVOLTAICE WITH PLUG-IN CARTRIDGE, EN SHORT-CIRCUIT CURRENT RATING ISCPV 100A, +, -, PE. CU CONTACT COMANDA DE LA DISTANTA

Cod producator Lovato: Surge Protection Device (SPD)
Tip produs: SA2
Operating voltage type: DC
Application: DC Power lines
Number of DIN modules: 2
Relay output: Da
SPD according to EN50539-11: Da
Rated operational voltage DC: VDC 600
Maximum continuous voltage U_{cpv} : V 600
Maximum discharge current (IEC) I_{max} 8/20 (L-N/N-PE): kA 30
Voltage protection level (IEC) U_p (L-N/N-PE):
Tripping time t_a (L-N/N-PE): ns
Thermal isolation protection: Da
Backup protection fuse (IEC) with $I_{sc} > 100A$: 100A gPV
Maximum short circuit current I_{scpv} : kA 0.1
Status indicator - operating / end of life: Frontal indication/Aux contact
Max altitude: m 2000
Mounting: Din rail
Tightening torque for terminals max: Nm 3
Conductor section - Flexible max (IEC): mm² 25
Conductor section - Rigid max (IEC): mm² 35
Greutate: g 325
Frontal IP degree: IP20
Conductor section max (IEC): mm² 1.5
Pret: 782,31 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/descarcator-tip-2-pentru-aplicatii-fotovoltaice-with-plug-in-cartridge-en-short-circuit-current-rating-iscpv-100a-pe-cu-contact-comanda-de-la-distanta-126776>