



**WAGO THT FEMALE HEADER; 0.4 X 1.3 MM SOLDER PIN; STRAIGHT; PIN SPACING  
5 MM; 5-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 16; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Numar poli: 5;

Total number of potentials: 5;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 5 mm / 0.197 inch;

Latime: 25 mm / 0.984 inch;

Inaltime: 19,8 mm / 0.78 inch;

Inaltime de la fata: 16,2 mm / 0.638 inch;

Adancime: 13,6 mm / 0.535 inch;

Lungimea pinului de contact: 3,6; mm

Solder pin dimensions: 0,4 x 1,3 mm;

Diametrul de gaurire cu toleranta: 1,5 (+0,1) mm;

Tip contact (pluggable connector): Conector mama/priza;

Connector (connection type): for PCB;

Mismatching protection: No;

Mating direction to the PCB: 90; °

PCB contact: THT;

Culoare: light gray;

Material group: I;

Material izolator: Polyphthalamide (PPA GF);

Flammability class per UL94: V0;

Contact material: Copper alloy;

Contact plating: tin-plated;

Fire load: 0,115; MJ

Greutate: 4,7; g

Temperatura lucru: -60 ... +100 °C;

Product Group: 26 (picoMAX);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4050821163664;

Customs tariff number: 85366990990;

Pret: 18,63 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tht-female-header-0-4-x-1-3-mm-solder-pin-straight-pin-spacing-5-mm-5-pole-light-gray-130360>