



### **WAGO CONDUCTOR SUPPORT, BASE; 5-POLE; 2,50 MM<sup>2</sup>; WHITE**

Tensiune nominala (III/2): 500; V

Tensiune nominala de supratensiune (III/2): 4; kV

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Certificari: UL 1059;

Strip length: 16 ... 18 mm / 0.63 ... 0.71 inch;

Numar poli: 5;

Numar tipuri de conexiuni: 1;

Latime: 30 mm / 1.181 inch;

Inaltime de la fata: 11.8 mm / 0.465 inch;

Adancime: 32 mm / 1.26 inch;

Culoare: white;

Material group: I;

Material izolator: Polyamide 66 (PA 66);

Flammability class per UL94: V0;

Clamping spring material: Chrome nickel spring steel (CrNi);

Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;

Fire load: 0,129; MJ

Greutate: 4,4; g

Temperature stability: 105; °C

Product Group: 8 (Misc. Chassis Mount Blocks);

Tip ambalare: bag;

Tara de origine: DE;

GTIN: 4017332145046;

Customs tariff number: 85369010000;

Pret: 1,85 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/conductor-support-base-5-pole-2-50-mm2-white-130399>