



**WAGO 2-CONDUCTOR GROUND TERMINAL BLOCK; 120 MM²; SUITABLE FOR EX E
II APPLICATIONS; LATERAL MARKER SLOTS; ONLY FOR DIN 35 X 15 RAIL;
POWER CAGE CLAMP; 120,00 MM²; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;
Tehnologie conexiune: POWER CAGE CLAMP;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Nominal cross-section: 120 mm²;
Solid conductor: 50 ... 120 mm² / 10 AWG ... 250 kcmil;
Stranded conductor: 50 ... 120 mm² / 1/0 AWG ... 250 kcmil;
Fine-stranded conductor: 50 ... 120 mm² / 1/0 AWG ... 250 kcmil;
Fine-stranded conductor; with insulated ferrule: 50 ... 120 mm² / 1/0 AWG ... 250 kcmil;
Fine-stranded conductor; with uninsulated ferrule: 50 ... 120 mm² / 1/0 AWG ... 250 kcmil;
Strip length: 45 ... 47 mm / 1.77 ... 1.85 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 32 mm / 1.26 inch;
Inaltime from upper-edge of DIN-rail: 116 mm / 4.567 inch;
Adancime: 132 mm / 5.197 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Side marking;
Culoare: green-yellow;
Material izolator: Polyamide 66 (PA 66);
Greutate: 623,6; g
Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4055143735018;
Customs tariff number: 85369010000;
Pret: 446,03 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-ground-terminal-block-120-mm2-suitable-for-ex-e-ii-applications-lateral-marker-slots-only-for-din-35-x-15-rail-power-cage-clamp-120-00-mm2-green-yellow-130438>