



**WAGO 4-LEVEL SAME POTENTIAL TERMINAL BLOCK; FOR 35 X 15 MOUNTING RAIL; 1,50 MM<sup>2</sup>; LIGHT GRAY**

Tensiune nominala (III/3): 250; V  
Tensiune nominala de supratensiune (III/3): 4; kV  
Curent nominal: 18; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG;  
Fine-stranded conductor: 0.08 ... 1.5 mm<sup>2</sup> / 28 ... 16 AWG;  
Strip length: 8 ... 10 mm / 0.31 ... 0.39 inch;  
Numar total de conexiuni: 16;  
Total number of potentials: 1;  
Numar nivele: 4;  
Wiring type: Front-entry wiring;  
Latime: 7.62 mm / 0.3 inch;  
Inaltime from upper-edge of DIN-rail: 44.5 mm / 1.752 inch;  
Adancime: 126 mm / 4.961 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking: 0-1-2-3--3-2-1-0;  
Marking level: Center marking;  
Culoare: light gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,556; MJ  
Greutate: 29,6; g  
Tip ambalare: BOX;

Tara de origine: DE;  
GTIN: 4045454190071;  
Customs tariff number: 85369010000;  
Pret: 52,07 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-level-same-potential-terminal-block-for-35-x-15-mounting-rail-1-50-mm2-light-gray-130702>