



**WAGO PCB TERMINAL BLOCK; 2.5 MM<sup>2</sup>; PIN SPACING 5 MM; 3-POLE; 2,50 MM<sup>2</sup>;  
GRAY**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/2): 800; V  
Tensiune nominala de supratensiune (III/2): 2,5; kV  
Curent nominal: 16; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Tehnologie conexiune: Screw clamp connection;  
Tip actionare: Operating tool;  
Solid conductor: 0.5 ... 2.5 mm<sup>2</sup> / 20 ... 14 AWG;  
Fine-stranded conductor: 0.5 ... 2.5 mm<sup>2</sup> / 20 ... 14 AWG;  
Strip length: 5 ... 7 mm / 0.2 ... 0.28 inch;  
Conductor connection direction to PCB: 0; °  
Numar poli: 3;  
Numar total de conexiuni: 3;  
Total number of potentials: 3;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Distanta intre pini: 10/10.16 mm / 0.394/0.4 inch;  
Latime: 10 mm / 0.394 inch;  
Inaltime de la fata: 11 mm / 0.433 inch;  
Adancime: 9 mm / 0.354 inch;  
PCB contact: THT;  
Solder pin arrangement: over the entire terminal strip, in line;  
Number of solder pins per potential: 1;  
Culoare: gray;  
Material group: I;

Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Greutate: 3,8; g  
Temperatura lucru: -60 ... +105 °C;  
Tip ambalare: BOX;  
Tara de origine: IN;  
GTIN: 4045454539979;  
Customs tariff number: 85369010000;  
Pret: 5,01 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pcb-terminal-block-2-5-mm2-pin-spacing-5-mm-3-pole-2-50-mm2-gray-130884>