



WAGO 1-CONDUCTOR/1-PIN CARRIER TERMINAL BLOCK; WITH SHIELD CONTACT; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 4 MM²; CAGE CLAMP®; 4,00 MM²; GRAY

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm²;

Solid conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 28.5 mm / 1.122 inch;

Adancime: 71.5 mm / 2.815 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,104; MJ

Greutate: 7,5; g
Product Group: 18 (X-COM-System);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821107415;
Customs tariff number: 85369010000;
Pret: 8,36 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-1-pin-carrier-terminal-block-with-shield-contact-for-din-rail-35-x-15-and-35-x-7-5-4-mm2-cage-clamp-4-00-mm2-gray-130886>