



### **WAGO SNAP-IN SOCKET; WITHOUT LOCKING LEVER; 2-POLE; COD. F; LIGHT GRAY**

Note on Contact Resistance:  $\approx 3m\Omega$  contact resistance

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 50; V

Tensiune nominala de supratensiune (III/3): 0,8; kV

Curent nominal: 3; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: PUSH WIRE®;

Tip actionare: Push-in;

Conductor diameter: 0,8 mm;

Strip length: 9 mm / 0.35 inch;

Note (strip length): see also packaging or instructions;

Numar poli: 2;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Conductor entry direction to mating direction: 0; °

Latime: 19,6 mm / 0.772 inch;

Inaltime: 19,6 mm / 0.772 inch;

Adancime: 29,5 mm / 1.161 inch;

Technologie: KNX;

Coding: F;

Mating force of a plug-in connection: approx. 10 ... 15 N;

Retention force of a plug-in connection: Locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;

Number of mating cycles: ?200;

Housing sheet thickness: 0,5 ... 2 mm / 0.02 ... 0.079 inch;

Tip montaj: Snap-in;

Marking: 1+ 2-;

Protection type: IP20;

Note on protection type: Only when mated and secured with a strain relief housing (These compact connectors are not designed for use in open, easily accessible areas.);

Potential marking: 1+ 2-;

Application: KNX;

Tip contact (pluggable connector): Conector mama/priza;

Connector (connection type): for conductor;

Mismating protection: Yes;

Locking of plug-in connection: locking lever;

Locking lever: yes;

Culoare: light gray;

Material izolator: Polyamide 66 (PA 66);

Fire class per EN 50575: Eca;

Clamping spring material: Chrome nickel spring steel (CrNi);

Contact material: Copper alloy (surface-treated);

Greutate: 4,5; g

Processing temperature: -5 ... +40 °C;

Continuous operating temperature: -35 ... +85 °C;

Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;

Product Group: 20 (WINSTA);

Tip ambalare: BOX;

Tara de origine: CH;

GTIN: 4045454420161;

Customs tariff number: 85366990990;

Pret: 36,97 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/snap-in-socket-without-locking-lever-2-pole-cod-f-light-gray-131099>