



WAGO 2-CONDUCTOR GROUND TERMINAL BLOCK; 50 MM²; SUITABLE FOR EX E II APPLICATIONS; LATERAL MARKER SLOTS; ONLY FOR DIN 35 X 15 RAIL; 2.3 MM THICK; COPPER; POWER CAGE CLAMP; 50,00 MM²; GREEN-YELLOW

Ratings per: IEC/EN 60947-7-2;
Tehnologie conexiune: POWER CAGE CLAMP;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 10 ... 50 mm² / 8 ... 1/0 AWG;
Stranded conductor: 10 ... 50 mm² / 8 ... 1/0 AWG;
Strip length: 30 mm / 1.18 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 20 mm / 0.787 inch;
Inaltime from upper-edge of DIN-rail: 87 mm / 3.425 inch;
Adancime: 94 mm / 3.701 inch;
Design: horizontal;
Tip montaj: DIN-35 rail;
Marking level: Side marking;
Culoare: green-yellow;
Material izolator: Polyamide 66 (PA 66);
Greutate: 186,5; g
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4055143418546;
Customs tariff number: 85369010000;
Pret: 179,21 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-ground-terminal-block-50-mm2-suitable-for-ex-e-ii-applications-lateral-marker-slots-only-for-din-35-x-15-rail-2-3-mm-thick-copper-power-cage-clamp-50-00-mm2-green-yellow-131102>