



**WAGO THR MALE HEADER; 1.4 MM Ø SOLDER PIN; ANGLED; PIN SPACING 5 MM;  
3-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 16; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 15; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Numar poli: 3;

Total number of potentials: 3;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 5 mm / 0.197 inch;

Latime: 17,2 mm / 0.677 inch;

Inaltime: 16,8 mm / 0.661 inch;

Inaltime de la fata: 14,4 mm / 0.567 inch;

Adancime: 19,5 mm / 0.768 inch;

Lungimea pinului de contact: 2,4; mm

Diametrul pinului de contact: 1,4; mm

Diametru placat prin gaura (THR): 1,6 (+0,1) mm;

Tip contact (pluggable connector): Conector tata/fisa;

Connector (connection type): for PCB;

Mismating protection: No;

Mating direction to the PCB: 0; °

Locking of plug-in connection: Locking latch;

PCB contact: THR;

Culoare: light gray;

Material group: I;

Material izolator: Polyphthalamide (PPA GF);

Flammability class per UL94: V0;

Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;

Fire load: 0,045; MJ

Greutate: 2,1; g

Temperatura lucru: -60 ... +100 °C;

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4050821395744;

Customs tariff number: 85366990990;

Pret: 3,70 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/thr-male-header-1-4-mm-oe-solder-pin-angled-pin-spacing-5-mm-3-pole-light-gray-131231>